DGF15N65CTL0


RoHS COMPLIANT

IGBT Discrete



V_{CE}	650	V
I_C	15	A
$V_{CE(SAT)}$ I_C=15A	1.40	V

Circuit



Applications

- Soft switching applications
- Air conditioning
- Motor drive inverter

Features

- High speed smooth switching device for hard & soft switching
- Maximum junction temperature 175℃
- Positive temperature coefficient
- High ruggedness, temperature stable

Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-Emitter Breakdown Voltage	V_{CE}	650	V
DC Collector Current, limited by T_{jmax} T_C= 25°C T_C= 100°C	I_C	 20 10	A
Diode Forward Current, limited by T_{jmax} T_C= 25°C T_C= 100°C	I_F	 20 10	A
Continuous Gate-Emitter Voltage	V_{GE}	±20	V
Transient Gate-Emitter Voltage (tp≤10μs,D<0.010)	V_{GE}	±30	V
Turn off Safe Operating Area V_{CE}≤ 600V, T_j≤ 150°C		45	A
Pulsed Collector Current, V_{GE}=15V, tp limited by T_{jmax}	I_{CM}	45	A
Short Circuit Withstand Time, VGE= 15V, VCE≤ 400V	Tsc	5	μs
Diode Pulsed Current, tp limited by T_{jmax}	I_{Fpuls}	45	A
Power Dissipation , Tj=175°C,Tc=25°C	P_{tot}	34	W

Operating Junction Temperature	T_j	-40...+175	°C
Storage Temperature	T_s	-55...+150	°C
Soldering Temperature, wave soldering 1.6mm (0.063in.) from case for 10s		260	°C

Electrical Characteristics of the IGBT（T_j= 25℃unless otherwise specified）:

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static						
Collector-Emitter Breakdown Voltage	BV_{CES}	V_{GE}=0V, I_C=250μA	650		-	V
Gate Threshold Voltage	$V_{GE(th)}$	V_{GE}=V_{CE}, I_C=1mA	5.0	5.8	6.5	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	V_{GE}=15V, I_C=15A T_j=25°C, T_j=125°C T_j=150°C		1.40 1.55 1.60	1.70	V
Zero Gate Voltage Collector Current	I_{CES}	V_{CE}=650V, V_{GE}=0V T_j= 25°C, T_j=150°C			0.25 1.00	mA
Gate-Emitter Leakage Current	I_{GES}	V_{CE}= 0V, V_{GE}= ± 20V			±200	nA

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic						
Input Capacitance	C_{ies}	V_{CE}= 25V, V_{GE}= 0V, f = 1MHz	-	0.88	-	nF
Output capacitance	C_{oes}		-	0.04	-	
Reverse Transfer Capacitance	C_{res}		-	0.01	-	
Gate Charge	Q_G	V_{CC}=300V,I_C=15A, V_{GE}=15V	-	0.069	-	uC
Short circuit collector current	$I_{C(SC)}$	V_{GE}=15V,t_{SC}≤5us V_{CC}=400V, $T_{j,start}$=25°C	-	110	-	A

Electrical Characteristics of the Diode（T_j= 25℃unless otherwise specified）:

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static						
Diode Forward Voltage	V_F	I_F= 15A T_j= 25°C, T_j= 125°C T_j= 150°C		1.90 1.70 1.60	2.40	V

Switching Characteristic, Inductive Load

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic , at T_j= 25℃						
Turn-on Delay Time	$t_{d(on)}$	T_j=25°C V_{CC}= 300V, I_C=15A, V_{GE}=-5V~15V, Rg=51Ω	-	10	-	ns
Rise Time	t_r		-	28	-	ns
Turn-on Energy	E_{on}		-	0.33	-	mJ
Turn-off Delay Time	$t_{d(off)}$		-	68	-	ns
Fall Time	t_f		-	138	-	ns
Turn-off Energy	E_{off}		-	0.16	-	mJ
Dynamic , at T_j= 125℃						
Turn-on Delay Time	$t_{d(on)}$	T_j=125°C V_{CC}= 300V, I_C=15A, V_{GE}=-5V~15V, Rg=51Ω	-	14	-	ns
Rise Time	t_r		-	36	-	ns
Turn-on Energy	E_{on}		-	0.38	-	mJ
Turn-off Delay Time	$t_{d(off)}$		-	69	-	ns
Fall Time	t_f		-	161	-	ns
Turn-off Energy	E_{off}		-	0.27	-	mJ
Dynamic , at T_j= 150℃						
Turn-on Delay Time	$t_{d(on)}$	T_j=150°C V_{CC}= 300V, I_C=15A, V_{GE}=-5V~15V, Rg=51Ω	-	16	-	ns
Rise Time	t_r		-	43	-	ns
Turn-on Energy	E_{on}		-	0.43	-	mJ
Turn-off Delay Time	$t_{d(off)}$		-	69	-	ns
Fall Time	t_f		-	182	-	ns
Turn-off Energy	E_{off}		-	0.32	-	mJ

Electrical Characteristics of the DIODE

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic , at T_j= 25℃						
Reverse Recovery Current	I_{rr}	I_F=15A, V_R=300V, -di/dt= 380A/μs,	-	6	-	A
Diode reverse recovery time	trr		-	197	-	ns
Reverse Recovery Charge	Q_{rr}		-	0.24	-	uC
Reverse Recovery Energy	Erec		-	0.06	-	mJ
Dynamic , at Tj= 125℃						
Reverse Recovery Current	I_{rr}	I_F=15A, V_R=300V, -di/dt= 380A/μs,	-	7	-	A
Diode reverse recovery time	trr		-	213	-	ns
Reverse Recovery Charge	Q_{rr}		-	0.58	-	uC
Reverse Recovery Energy	Erec		-	0.11	-	mJ
Dynamic , at Tj= 150℃						
Reverse Recovery Current	I_{rr}	I_F=15A, V_R=300V, -di/dt= 380A/μs,	-	8	-	A
Diode reverse recovery time	trr		-	221	-	ns
Reverse Recovery Charge	Q_{rr}		-	0.71	-	uC
Reverse Recovery Energy	Erec		-	0.14	-	mJ

Thermal Resistance

Parameter	Symbol	Max. Value	Unit
IGBT Thermal Resistance, Junction - Case	R_{th}(j-c)	4.4	K/W
Diode Thermal Resistance, Junction - Case	R_{th}(j-c)	4.8	K/W
Thermal Resistance, Junction - Ambient	R_{th}(j-a)	60	K/W




Fig1.IGBT Output Characteristics(25℃)




Fig2.IGBT Output Characteristics(150℃)




Fig3.Diode Foward Characteristics




Fig4.IGBT Transfer Characteristics




Fig5.IGBT Switching Loss vs.Ic(150°C)




Fig6.IGBT Switching Loss vs.Rg(150°C)




Fig7.Diode Switching Loss(Erec) vs.I_F(150°C)




Fig8.Diode Switching Loss(Erec)vs.Rg(150°C)




Fig 9. IGBT Transient Thermal Impedance





Fig10.Diode Transient Thermal Impedance


Circuit Diagram





Package Outline Information

CASE: TO-220F package information



SYMBOL	单位：mm			SYMBOL	单位：mm			SYMBOL	单位：mm		
	MIN	NOM	MAX		MIN	NOM	MAX		MIN	NOM	MAX
A	4.40	4.50	4.60	E	10.00	10.16	10.30	ΦP2	3.30	3.40	3.50
A1	2.34	2.54	2.74	E1	9.94	10.06	10.20	θ1	3°	5°	7°
A2	2.66	2.76	2.86	E2	9.40	9.50	9.60	θ2	42°	45°	48°
A3		1.0REF		F1	1.40	1.50	1.60				
b1	1.18	1.20	1.24	F2	13.80	13.90	14.00				
b2	0.75	0.80	0.85	F3	3.20	3.30	3.40				
b3	1.22	1.30	1.38	G1	6.90	7.00	7.10				
C	0.45	0.50	0.55	K1	0.65	0.70	0.75				
D	15.67	15.87	16.07	L	12.78	12.98	13.18				
D1	9.04	9.12	9.20	L1	3.40	3.50	3.60				
e	2.50	2.54	2.58	Q		6.50REF					
e1		5.08REF		ΦP	3.08	3.18	3.28				

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.