
DGW40N120CTL1A1


RoHS COMPLIANT



IGBT Discrete

V_{CE}	1200	V
I_C	40	A
$V_{CE(SAT)}$ I_C=40A	1.65	V

Circuit



Applications

- Inverter for motor drive
- AC and DC servo drive amplifier

Features

- High breakdown voltage to 1200V for improved reliability
- Maximum junction temperature 175℃
- Positive temperature coefficient
- Including fast & soft recovery anti-parallel FWD
- High short circuit capability(10us)

Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-Emitter Breakdown Voltage	V_{CE}	1200	V
DC Collector Current, limited by T_{jmax} T_C= 25°C T_C= 100°C	I_C	80 40	A
Diode Forward Current, limited by T_{jmax} T_C= 25°C T_C= 100°C	I_F	80 40	A
Continuous Gate-Emitter Voltage	V_{GE}	±20	V
Transient Gate-Emitter Voltage (tp≤10μs,D<0.010)	V_{GE}	±30	V
Turn off Safe Operating Area V_{CE}≤1200V, T_j≤ 150°C		120	A
Pulsed Collector Current, V_{GE}=15V, tp limited by T_{jmax}	I_{CM}	120	A
Diode Pulsed Current, tp limited by T_{jmax}	I_{Fpuls}	120	A
Short Circuit Withstand Time, V_{GE}= 15V, V_{CC}=600V， V_{CEM}≤1200V	T_{sc}	10	μs
Power Dissipation , Tj=175°C， Tc=25°C	P_{tot}	320	W

Operating Junction Temperature	T_j	-40...+175	°C
Storage Temperature	T_s	-55...+150	°C
Soldering Temperature, wave soldering 1.6mm (0.063in.) from case for 10s		260	°C

Electrical Characteristics of the IGBT（T_j= 25℃unless otherwise specified）:

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static						
Collector-Emitter Breakdown Voltage	BV_{CES}	V_{GE}=0V, I_C=250μA	1200		-	V
Gate Threshold Voltage	$V_{GE(th)}$	V_{GE}=V_{CE}, I_C=1.0mA	5.2	5.8	6.5	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	V_{GE}=15V, I_C=40A T_j=25°C, T_j=125°C T_j=150°C		1.65 1.95 2.05	1.95	V
Zero Gate Voltage Collector Current	I_{CES}	V_{CE}=1200V, V_{GE}=0V T_j= 25°C, T_j=150°C			0.25 4	mA
Gate-Emitter Leakage Current	I_{GES}	V_{CE}= 0V, V_{GE}= ± 20V			100	nA

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic						
Input Capacitance	C_{ies}	V_{CE}= 25V, V_{GE}= 0V, f = 1MHz	-	4.29	-	nF
Output Capacitance	C_{oes}		-	0.12	-	
Reverse Transfer Capacitance	C_{res}		-	0.04	-	
Gate Charge	Q_G	V_{CC}=600V,I_C=40A, V_{GE}=15V	-	0.27	-	uC
Short Circuit Collector Current	I_{SC}	V_{GE}=15V, tsc≤10us, Vcc=600V	-	264	-	A

Electrical Characteristics of the Diode（T_j= 25℃unless otherwise specified）:

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static						
Diode Forward Voltage	V_F	I_F= 40A T_j= 25°C, T_j= 125°C T_j= 150°C		2.00 1.90 1.80	2.60	V

Switching Characteristic, Inductive Load

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic , at T_j= 25℃						
Turn-on Delay Time	$t_{d(on)}$	V_{CC}= 600V, I_C=40A, V_{GE}= -5V~15V, R_g=20Ω	-	93	-	ns
Rise Time	t_r		-	93	-	ns
Turn-on Energy	E_{on}		-	3.92	-	mJ
Turn-off Delay Time	$t_{d(off)}$		-	269	-	ns
Fall Time	t_f		-	190	-	ns
Turn-off Energy	E_{off}		-	2.53	-	mJ
Dynamic , at T_j= 125℃						
Turn-on Delay Time	$t_{d(on)}$	V_{CC}= 600V, I_C=40A, V_{GE}= -5V~15V, R_g=20Ω	-	87	-	ns
Rise Time	t_r		-	96	-	ns
Turn-on Energy	E_{on}		-	4.33	-	mJ
Turn-off Delay Time	$t_{d(off)}$		-	288	-	ns
Fall Time	t_f		-	277	-	ns
Turn-off Energy	E_{off}		-	3.32	-	mJ
Dynamic , at T_j= 150℃						
Turn-on Delay Time	$t_{d(on)}$	V_{CC}= 600V, I_C=40A, V_{GE}= -5V~15V, R_g=20Ω	-	84	-	ns
Rise Time	t_r		-	99	-	ns
Turn-on Energy	E_{on}		-	4.44	-	mJ
Turn-off Delay Time	$t_{d(off)}$		-	300	-	ns
Fall Time	t_f		-	313	-	ns
Turn-off Energy	E_{off}		-	3.58	-	mJ

Electrical Characteristics of the DIODE

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic , at T_j= 25℃						
Reverse Recovery Current	I_{rr}	I_F=40A, V_R=600V, di/dt= -500A/μs	-	11	-	A
Diode reverse recovery time	trr		-	225	-	ns
Reverse Recovery Charge	Q_{rr}		-	1.29	-	uC
Reverse Recovery Energy	Erec		-	0.33	-	mJ
Dynamic , at Tj= 125℃						
Reverse Recovery Current	I_{rr}	I_F=40A, V_R=600V, di/dt= -500A/μs	-	15	-	A
Diode reverse recovery time	trr		-	315	-	ns
Reverse Recovery Charge	Q_{rr}		-	3.58	-	uC
Reverse Recovery Energy	Erec		-	1.07	-	mJ
Dynamic , at Tj= 150℃						
Reverse Recovery Current	I_{rr}	I_F=40A, V_R=600V, di/dt= -500A/μs	-	16	-	A
Diode reverse recovery time	trr		-	344	-	ns
Reverse Recovery Charge	Q_{rr}		-	4.11	-	uC
Reverse Recovery Energy	Erec		-	1.23	-	mJ

Thermal Resistance

Parameter	Symbol	Max. Value	Unit
IGBT Thermal Resistance, Junction - Case	R_{θ}(j-c)	0.47	K/W
Diode Thermal Resistance, Junction - Case	R_{θ}(j-c)	1.00	K/W
Thermal Resistance, Junction - Ambient	R_{θ}(j-a)	40	K/W




Fig1. Power dissipation as a function of case temperature (Tj≤175℃)




Fig2. Collector current as a function of case temperature(Vge≥15V, Tj≤175℃)




Fig3. Typical output characteristic (Tj=25°C)




Fig4. Typical output characteristic (Tj=150°C)




Fig5. Typical transfer characteristic (Vce=20V)




Fig6. Typical collector-emmiter saturation voltage as a function of junction temperature(Vge=15V)




Fig7. Typical switching times as a function of collect current




Fig8. Typical switching times as a fuction of gate resistance




Fig9. Typical switching times as a fuction of junction temperature




Fig10. Gate-emitter threshold voltage as a fuction of junction temperature




Fig11. Typical switching energy losses as a fuction of collect current




Fig12. Typical switching energy losses as a fuction of gate resistance




Fig13. Typical switching energy losses as a fuction of junction temperature




Fig14. Typical switching energy losses as a fuction of collector-emitter voltage




Fig15. Typical capacitance as a function of collector-emitter voltage




Fig 16. IGBT Transient Thermal Impedance




Fig 17. Diode Transient Thermal Impedance




Fig18. Diode forawrd current as a function of foraward voltage





Fig19. Diode forawrd voltage as a function of junction temperature


Circuit Diagram





Package Outline Information

CASE: TO 247



TO-247AB		
Dim	Min	Max
A	4.80	5.20
A1	2.21	2.61
A2	1.85	2.15
b	1.0	1.4
b2	1.91	2.21
C	0.5	0.7
D	20.70	21.30
D1	16.25	16.85
E	15.50	16.10
E1	13.0	13.6
E2	4.80	5.20
E3	2.30	2.70
L	19.62	20.22
L1	-	4.30
ΦP	3.40	3.80
ΦP1	-	7.30
S	6.15TYP	
H1	5.44TYP	
b3	2.80	3.20

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.