

N-Channel Enhancement Mode Field Effect Transistor




Top View



Bottom View

SOT-23



Product Summary

- V_{DS} 60V
- I_D 340mA
- $R_{DS(ON)}$(at V_{GS}=10V) ＜2.5ohm
- $R_{DS(ON)}$(at V_{GS}=4.5V) ＜3.0ohm

General Description

- Trench Power MV MOSFET technology
- Voltage controlled small signal switch
- Low input Capacitance
- Fast Switching Speed
- Low Input / Output Leakage

Applications

- Battery operated systems
- Solid-state relays
- Direct logic-level interface：TTL/CMOS

■ Absolute Maximum Ratings (T_A=25℃unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		V_{DS}	60	V
Gate-source Voltage		V_{GS}	±20	V
Drain Current	T_A=25℃ @ Steady State	I_D	340	mA
	T_A=70℃ @ Steady State		272	
Pulsed Drain Current [A]		I_{DM}	1.5	A
Total Power Dissipation @ T_A=25℃		P_D	350	mW
Thermal Resistance Junction-to-Ambient @ Steady State [B]		$R_{\theta JA}$	357	℃/ W
Junction and Storage Temperature Range		T_J ,T_{STG}	-55～+150	℃

■ Ordering Information (Example)

PREFERED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
2N7002	F2	7002.	3000	30000	120000	7“ reel

■ Electrical Characteristics (T_J=25℃ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}= 0V, I_D=250μA	60			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=60V,V_{GS}=0V			1	μA
Gate-Body Leakage Current	I_{GSS1}	V_{GS}= ±20V, V_{DS}=0V			±100	nA
	I_{GSS2}	V_{GS}= ±10V, V_{DS}=0V			±50	nA
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}= V_{GS}, I_D=250μA	1	1.5	2.5	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	V_{GS}= 10V, I_D=300mA		1.2	2.5	Ω
		V_{GS}= 4.5V, I_D=200mA		1.3	3.0	
Forward Transconductance	gfs	V_{DS}=10 V, I_D=200mA	80			ms
Diode Forward Voltage	V_{SD}	I_S=300mA,V_{GS}=0V			1.2	V
Maximum Body-Diode Continuous Current	I_S				340	mA
Dynamic Parameters						
Input Capacitance	C_{iss}	V_{DS}=30V,V_{GS}=0V,f=1MHz		27.5		pF
Output Capacitance	C_{oss}			2.75		
Reverse Transfer Capacitance	C_{rss}			1.9		
Switching Parameters						
Total Gate Charge	Q_g	V_{GS}=10V,V_{DS}=30V,I_D=0.3A		1.6		nC
Gate-Source Charge	Q_{gs}			0.47		
Gate-Drain Charge	Q_{gd}			0.25		
Reverse Recovery Charge	Q_{rr}	I_F=0.3A, di/dt=-100A/us		2.5		
Reverse Recovery Time	t_{rr}			11.5		ns
Turn-on Delay Time	$t_{D(on)}$	V_{GS}=10V,V_{DD}=30V, I_D=300mA, R_{GEN}=6Ω		3.3		
Turn-on Rise Time	t_r			19		
Turn-off Delay Time	$t_{D(off)}$			9.6		
Turn-off fall Time	t_f			49		

A. Pulse Test: Pulse Width≤300us,Duty cycle ≤2%.
B. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch.

■ Typical Performance Characteristics




Figure1. Output Characteristics




Figure2. Transfer Characteristics




Figure3. Capacitance Characteristics




Figure4. Gate Charge




Figure5. Drain-Source on Resistance




Figure6. Drain-Source on Resistance




Figure7. Safe Operation Area






Figure8. Switching wave


■ SOT-23 Package information




TOP VIEW



SIDE VIEW



SIDE VIEW



UNIT：mm

SUGGESTED SOLDER PAD LAYOUT

DIMENSIONS				
SYMBOL	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.045	0.900	1.150
A1	0.000	0.004	0.000	0.100
A2	0.035	0.041	0.900	1.050
b	0.012	0.020	0.300	0.500
c	0.004	0.008	0.100	0.200
D	0.110	0.118	2.800	3.000
E	0.047	0.055	1.200	1.400
E1	0.089	0.100	2.250	2.550
e	0.037TYP		0.950TYP	
e1	0.071	0.079	1.800	2.000
L	0.022REF		0.550REF	
L1	0.012	0.020	0.300	0.500
θ	0°	8°	0°	8°

NOTE:
1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability,or infringement of any patent, copyright, or other intellectual property right.