
# N-Channel Enhancement Mode Field Effect Transistor




## Product Summary

- $V_{DS}$ 80V
- $I_D$ 110A
- $R_{DS(ON)}$( at $V_{GS}$=10V) ＜6mΩ
- $R_{DS(ON)}$( at $V_{GS}$=4.5V) ＜7mΩ
- 100% EAS Tested
- 100% ▽$V_{DS}$ Tested

## General Description

- Split gate trench MOSFET technology
- Excellent package for heat dissipation
- High density cell design for low $R_{DS(ON)}$
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

## Applications

- Power switching application
- Uninterruptible power supply
- DC-DC convertor

## ■ Absolute Maximum Ratings ($T_A$=25℃ unless otherwise noted)

| Parameter | | Symbol | Limit | Unit |
|---|---|---|---|---|
| Drain-source Voltage | | $V_{DS}$ | 80 | V |
| Gate-source Voltage | | $V_{GS}$ | ±20 | V |
| Drain Current | $T_A$=25℃ | $I_D$ | 13 | A |
| | $T_A$=100℃ | | 8 | |
| | $T_C$=25℃ | | 110 | |
| | $T_C$ =100℃ | | 69 | |
| Pulsed Drain Current [A] | | $I_{DM}$ | 400 | A |
| Avalanche energy [B] | | EAS | 361 | mJ |
| Total Power Dissipation [C] | $T_A$=25℃ | $P_D$ | 2.5 | W |
| | $T_A$=100℃ | | 1 | |
| | $T_C$=25℃ | | 83 | |
| | $T_C$ =100℃ | | 33 | |
| Junction and Storage Temperature Range | | $T_J$ ,$T_{STG}$ | -55～+150 | ℃ |

## ■ Thermal resistance

| Parameter | | Symbol | Typ | Max | Units |
|---|---|---|---|---|---|
| Thermal Resistance Junction-to-Ambient [D] | Steady-State | $R_{\theta JA}$ | 40 | 50 | ℃/W |
| Thermal Resistance Junction-to-Case | Steady-State | $R_{\theta JC}$ | 1.25 | 1.5 | |

## ■ Ordering Information (Example)

| PREFERED P/N | PACKING CODE | Marking | MINIMUM PACKAGE(pcs) | INNER BOX QUANTITY(pcs) | OUTER CARTON QUANTITY(pcs) | DELIVERY MODE |
|---|---|---|---|---|---|---|
| D110G08A | F1/F2 | D110G08A | 2500 | / | 25000 | 13“ reel |

## ■ Electrical Characteristics ($T_J$=25℃ unless otherwise noted)

| Parameter | Symbol | Conditions | Min | Typ | Max | Units |
|---|---|---|---|---|---|---|
| **Static Parameter** | | | | | | |
| Drain-Source Breakdown Voltage | $BV_{DSS}$ | $V_{GS}$= 0V, $I_D$=250μA | 80 | - | - | V |
| Zero Gate Voltage Drain Current | $I_{DSS}$ | $V_{DS}$=80V, $V_{GS}$=0V | - | - | 1 | μA |
| | | $V_{DS}$=80V, $V_{GS}$=0V, Tj=150℃ | - | - | 100 | |
| Gate-Body Leakage Current | $I_{GSS}$ | $V_{GS}$= ±20V, $V_{DS}$=0V | - | - | ±100 | nA |
| Gate Threshold Voltage | $V_{GS(th)}$ | $V_{DS}$= $V_{GS}$, $I_D$=250μA | 1.4 | 1.8 | 2.5 | V |
| Static Drain-Source On-Resistance | $R_{DS(ON)}$ | $V_{GS}$=10V, $I_D$=55A | - | 4.2 | 6 | mΩ |
| | | $V_{GS}$=10V, $I_D$=20A | | 4.2 | 6 | |
| | | $V_{GS}$=4.5V, $I_D$=55A | - | 5.5 | 7 | |
| Diode Forward Voltage | $V_{SD}$ | $I_S$=55A, $V_{GS}$=0V | - | 0.9 | 1.2 | V |
| Gate resistance | $R_G$ | f=1MHz | - | 1.9 | - | Ω |
| Maximum Body-Diode Continuous Current | $I_S$ | | - | - | 110 | A |
| **Dynamic Parameters** | | | | | | |
| Input Capacitance | $C_{iss}$ | $V_{DS}$=40V, $V_{GS}$=0V, f=1MHz | - | 6500 | - | pF |
| Output Capacitance | $C_{oss}$ | | - | 850 | - | |
| Reverse Transfer Capacitance | $C_{rss}$ | | - | 35 | - | |
| **Switching Parameters** | | | | | | |
| Total Gate Charge | $Q_g$ | $V_{GS}$=10V, $V_{DS}$=40V, $I_D$=55A | - | 95 | - | nC |
| Gate-Source Charge | $Q_{gs}$ | | - | 18 | - | |
| Gate-Drain Charge | $Q_{gd}$ | | - | 16 | - | |
| Reverse Recovery Charge | $Q_{rr}$ | $I_F$=55A, di/dt=400A/us | - | 83 | - | nC |
| Reverse Recovery Time | $t_{rr}$ | | - | 33 | - | ns |
| Turn-on Delay Time | $t_{D(on)}$ | $V_{GS}$=10V, $V_{DD}$=40V, $I_D$=55A $R_{GEN}$=2.2Ω | - | 17 | - | ns |
| Turn-on Rise Time | $t_r$ | | - | 90 | - | |
| Turn-off Delay Time | $t_{D(off)}$ | | - | 47 | - | |
| Turn-off fall Time | $t_f$ | | - | 10.5 | - | |

A. Repetitive rating; pulse width limited by max. junction temperature.
B. $T_J$=25℃, $V_{DD}$=50V, $V_G$=10V, $R_G$=25Ω, L=0.5mH, IAS=38A.
C. $P_d$ is based on max. junction temperature, using junction-case thermal resistance.
D. The value of $R_{\theta JA}$ is measured with the device mounted on the minimum recommend pad size, in the still air environment with $T_A$ =25℃. The maximum allowed junction temperature of 150℃. The value in any given application depends on the user's specific board design.

## ■ Typical Electrical and Thermal Characteristics Diagrams





Figure 1. Output Characteristics





Figure 2. Transfer Characteristics





Figure 3. Capacitance Characteristics





Figure 4. Gate Charge





Figure 5. On-Resistance vs Gate to Source Voltage





Figure 6. Normalized On-Resistance





Figure 7. $R_{DS(on)}$ VS Drain Current





Figure 8. Forward characteristics of reverse diode





Figure 9. Normalized breakdown voltage





Figure 10. Normalized Threshold voltage





Figure 11. Current dissipation





Figure 12. Power dissipation





Figure 13. Maximum Transient Thermal Impedance







Figure 14. Safe Operation Area


## ■ TO-252-B Package information





TOP VIEW




SIDE VIEW




BOTTOM VIEW




SUGGESTED SOLDER PAD LAYOUT

UNIT：mm

| DIMENSIONS | | | | | | |
|---|---|---|---|---|---|---|
| SYMBOL | INCHES | | | Millimeter | | |
| | MIN. | NOM. | MAX. | MIN. | NOM. | MAX. |
| A1 | 0.000 | --- | 0.008 | 0.000 | --- | 0.200 |
| A2 | 0.087 | 0.091 | 0.094 | 2.200 | 2.300 | 2.400 |
| A3 | 0.035 | 0.039 | 0.043 | 0.900 | 1.000 | 1.100 |
| b | 0.026 | 0.030 | 0.034 | 0.660 | 0.760 | 0.860 |
| c | 0.018 | 0.020 | 0.023 | 0.460 | 0.520 | 0.580 |
| D | 0.256 | 0.260 | 0.264 | 6.500 | 6.600 | 6.700 |
| D1 | 0.203 | 0.209 | 0.215 | 5.150 | 5.300 | 5.450 |
| D2 | 0.181 | 0.189 | 0.195 | 4.600 | 4.800 | 4.950 |
| E | 0.390 | 0.398 | 0.406 | 9.900 | 10.100 | 10.300 |
| E1 | 0.236 | 0.240 | 0.244 | 6.000 | 6.100 | 6.200 |
| E2 | 0.203 | 0.209 | 0.215 | 5.150 | 5.300 | 5.450 |
| e | 0.090BSC | | | 2.286BSC | | |
| L | 0.049 | 0.059 | 0.069 | 1.250 | 1.500 | 1.750 |
| L1 | 0.035 | --- | 0.050 | 0.900 | --- | 1.270 |
| L2 | 0.055 | --- | 0.075 | 1.400 | --- | 1.900 |
| L3 | 0.024 | 0.031 | 0.039 | 0.600 | 0.800 | 1.000 |
| L4 | 0.114REF | | | 2.900REF | | |
| θ | 0° | --- | 10° | 0° | --- | 10° |

NOTE:
1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.

## Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.