

N-Channel Enhancement Mode Field Effect Transistor




Top View



Bottom View

PDFN5060-8L



Product Summary

- V_{DS} 30V
- I_D 105A
- $R_{DS(ON)}$(at V_{GS}= 10V) ＜3.0mohm
- $R_{DS(ON)}$(at V_{GS}= 4.5V) ＜4.0mohm
- 100% EAS Tested
- 100% ▽V_{DS} Tested

General Description

- Trench Power MV MOSFET technology
- Excellent package for heat dissipation
- High density cell design for low $R_{DS(ON)}$
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

Applications

- DC-DC Converters
- Power management functions
- Backlighting

■ Absolute Maximum Ratings (T_A=25℃unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		V_{DS}	30	V
Gate-source Voltage		V_{GS}	±20	V
Drain Current	T_C=25℃	I_D	105	A
	T_C=100℃		66	
Pulsed Drain Current [A]		I_{DM}	415	A
Total Power Dissipation @ T_C=25℃		P_D	70	W
Single Pulse Avalanche Energy [B]		E_{AS}	507	mJ
Thermal Resistance Junction-to-Case		$R_{\theta JC}$	1.8	℃/ W
Thermal Resistance Junction-to-Ambient		$R_{\theta JA}$	50	℃/ W
Junction and Storage Temperature Range		T_J ,T_{STG}	-55～+150	℃

■ Ordering Information (Example)

PREFERED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
G105N03A	F1	G105N03A	5000	10000	100000	13“ reel

■ Electrical Characteristics (T_J=25℃ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}= 0V, I_D=250μA	30			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=30V,V_{GS}=0V			1	μA
Gate-Body Leakage Current	I_{GSS}	V_{GS}= ±20V, V_{DS}=0V			±100	nA
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}= V_{GS}, I_D=250μA	1.0	1.5	2.5	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	V_{GS}= 10V, I_D=20A		2.45	3.0	mΩ
		V_{GS}= 4.5V, I_D=15A		2.9	4.0	
Diode Forward Voltage	V_{SD}	I_S=20A,V_{GS}=0V		0.85	1.2	V
Gate resistance	R_G	f=1MHz	-	1.5	-	Ω
Maximum Body-Diode Continuous Current	I_S				105	A
Dynamic Parameters						
Input Capacitance	C_{iss}	V_{DS}=15V,V_{GS}=0V,f=1MHZ		4401		pF
Output Capacitance	C_{oss}			581		
Reverse Transfer Capacitance	C_{rss}			439		
Switching Parameters						
Total Gate Charge	Q_g	V_{GS}=10V,V_{DS}=20V,I_D=20A		49.5		nC
Gate-Source Charge	Q_{gs}			10.4		
Gate-Drain Charge	Q_{gd}			8.9		
Reverse Recovery Charge	Q_{rr}	I_F=20A, di/dt=500A/us		7.5		
Reverse Recovery Time	t_{rr}			23		ns
Turn-on Delay Time	$t_{D(on)}$	V_{GS}=10V, V_{DD}=15V, I_D=2A,R_{GEN}=3Ω		13		
Turn-on Rise Time	t_r			22		
Turn-off Delay Time	$t_{D(off)}$			63		
Turn-off fall Time	t_f			33		

A. Pulse Test: Pulse Width≤300us,Duty cycle ≤2%.

B. $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance, where the case thermal reference is defined as the solder mounting surface of the drain pins. $R_{\theta JC}$ is guaranteed by design, while $R_{\theta JA}$ is determined by the board design. The maximum rating presented here is based on mounting on a 1 in 2 pad of 2oz copper.

■ Typical Performance Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance vs. Junction Temperature




Figure 5. Capacitance Characteristics




Figure 6. Gate Charge




Figure 7. Safe Operation Area




Figure 8. Maximum Continuous Drain Current vs Case Temperature






Figure 9. Normalized Maximum Transient Thermal Impedance


■ PDFN5060-8L-B-1.1MM Package Information




Top View
正面视图



Bottom View
背面视图



Side View
侧面视图



Suggested Solder Pad Layout
Top View

SYMBOL	MILLIMETER		
	MIN	NOM	MAX
D	5.15	5.35	5.55
E	5.95	6.15	6.35
A	1.00	1.10	1.20
A1		0.254 BSC	
A2			0.10
D1	3.92	4.12	4.32
E1	3.52	3.72	3.92
D2	5.00	5.20	5.40
E2	5.66	5.86	6.06
E3		0.254 REF	
E4		0.21 REF	
L1	0.56	0.66	0.76
L2		0.50 BSC	
b	0.31	0.41	0.51
e		1.27 BSC	

Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.10mm.
3.The pad layout is for reference purposes only.

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.