

# P-Channel Enhancement Mode Field Effect Transistor




Top View



Bottom View

SOT-23




## Product Summary

- $V_{DS}$ -30V
- $I_D$ -2.7A
- $R_{DS(ON)}$( at $V_{GS}$=-10V) ＜85mΩ
- $R_{DS(ON)}$( at $V_{GS}$=-4.5V) ＜125mΩ
- ESD Protected Up to 2KV (HBM)

## General Description

- High Speed switching
- High density cell design for low $R_{DS(ON)}$
- Moisture Sensitivity Level 1
- Epoxy Meets UL94 V-0 Flammability Rating
- Halogen Free

## Applications

- PWM applications
- Power management
- Load switch

## ■ Limiting Values

| Parameter | Conditions | | Symbol | Min | Max | Unit |
|---|---|---|---|---|---|---|
| Drain-source Voltage | $T_J$≥25°C;$T_J$≤150°C | | $V_{DS}$ | - | -30 | V |
| Gate-source Voltage | $T_J$≤150°C;DC | | $V_{GS}$ | -20 | 20 | |
| Continuous Drain Current (Note 1,2) | Steady-State | $T_A$=25℃,$V_{GS}$=-10V | $I_D$ | - | -2.7 | A |
| | | $T_A$=100℃,$V_{GS}$=-10V | | - | -1.9 | |
| Pulsed Drain Current | $T_A$=25℃,$t_p$≤10μs | | $I_{DM}$ | - | -22 | |
| Maximum Body-Diode Continuous Current | $T_A$=25℃ | | $I_S$ | - | -1.3 | |
| Total Power Dissipation (Note 1,2) | Steady-State | $T_A$=25℃ | $P_D$ | - | 0.95 | W |
| | | $T_A$=100℃ | | - | 0.38 | |
| Junction and Storage Temperature Range | | | $T_J$ ,$T_{STG}$ | -55 | 150 | ℃ |

## ■Thermal Resistance

| Parameter | | Symbol | Typ | Max | Units |
|---|---|---|---|---|---|
| Thermal Resistance Junction-to-Ambient (Note 2) | Steady-State | $R_{\theta JA}$ | - | 131 | ℃/W |

## ■ Ordering Information (Example)

| PREFERED P/N | PACKING CODE | Marking | MINIMUM PACKAGE(pcs) | INNER BOX QUANTITY(pcs) | OUTER CARTON QUANTITY(pcs) | DELIVERY MODE |
|---|---|---|---|---|---|---|
| L085P03AK | F2 | 08503. | 3000 | 30000 | 120000 | 7“ reel |

## ■ Electrical Characteristics

| Parameter | Symbol | Conditions | Min | Typ | Max | Units |
|---|---|---|---|---|---|---|
| **Static Parameter** | | | | | | |
| Drain-Source Breakdown Voltage | $BV_{DSS}$ | $V_{GS}$=0V,$I_D$=-250μA,Tj=25℃ | -30 | - | - | V |
| Zero Gate Voltage Drain Current | $I_{DSS}$ | $V_{DS}$=-30V,$V_{GS}$=0V,Tj=25℃ | - | - | -1 | μA |
| | | $V_{DS}$=-30V,$V_{GS}$=0V,Tj=150℃ | - | - | -100 | |
| Gate-Source Leakage Current | $I_{GSS}$ | $V_{GS}$=±20V,$V_{DS}$=0V,Tj=25℃ | - | - | ±10 | uA |
| Gate Threshold Voltage | $V_{GS(th)}$ | $V_{DS}$=$V_{GS}$,$I_D$=-250μA,Tj=25℃ | -1.0 | -1.5 | -2.0 | V |
| Static Drain-Source On-Resistance | $R_{DS(ON)}$ | $V_{GS}$=-10V,$I_D$=-1.8A,Tj=25℃ | - | 66 | 85 | mΩ |
| | | $V_{GS}$=-4.5V,$I_D$=-0.9A,Tj=25℃ | - | 96 | 125 | mΩ |
| Diode Forward Voltage | $V_{SD}$ | $I_S$=-1.8A,$V_{GS}$=0V,Tj=25℃ | - | -0.86 | -1.2 | V |
| Gate Resistance | $R_G$ | f=1MHz,Tj=25℃ | - | 19 | - | Ω |
| **Dynamic Parameters** | | | | | | |
| Input Capacitance | $C_{iss}$ | $V_{DS}$=-15V,$V_{GS}$=0V,f=1MHz,Tj=25℃ | - | 213 | - | pF |
| Output Capacitance | $C_{oss}$ | | - | 40 | - | |
| Reverse Transfer Capacitance | $C_{rss}$ | | - | 29 | - | |
| **Switching Parameters** | | | | | | |
| Total Gate Charge | $Q_g$ | $V_{GS}$=-10V,$V_{DS}$=-15V,$I_D$=-1.8A,Tj=25℃ | - | 5.5 | - | nC |
| Gate-Source Charge | $Q_{gs}$ | | - | 0.25 | - | |
| Gate-Drain Charge | $Q_{gd}$ | | - | 0.85 | - | |
| Reverse Recovery Charge | $Q_{rr}$ | $I_F$=-1.8A,di/dt=100A/μs,$V_{GS}$=0V, $V_R$=-15V,Tj=25℃ | - | 18 | - | nC |
| Reverse Recovery Time | $t_{rr}$ | | - | 45 | - | ns |
| Turn-on Delay Time | $t_{D(on)}$ | $V_{GS}$=-10V,$V_{DS}$=-15V,$I_D$=-1.8A,$R_L$=8.3Ω, $R_{GEN}$=3Ω,Tj=25℃ | - | 4.5 | - | ns |
| Turn-on Rise Time | $t_r$ | | - | 2.3 | - | |
| Turn-off Delay Time | $t_{D(off)}$ | | - | 16 | - | |
| Turn-off Fall Time | $t_f$ | | - | 11 | - | |

Note：

1. The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.
2. The value of $R_{\theta JA}$ is measured with the device mounted on the 40mm*40mm*1.1mm single layer FR-4 PCB board with 1 $in^2$ pad of 2oz. Copper, in the still air environment with $T_A$=25℃.The maximum allowed junction temperature of 150℃. The value in any given application depends on the user's specific board design.
3. Thermal resistance from junction to soldering point (on the exposed drain pad)

## ■Typical Electrical and Thermal Characteristics Diagrams





Figure 1. Output Characteristics; typical values





Figure 2. Transfer Characteristics; typical values





Figure 3. Capacitance Characteristics; typical values





Figure 4. Gate Charge; typical values





Figure 5. On-Resistance vs Gate to Source Voltage; typical values





Figure 6. Normalized On-Resistance





Figure 7. $R_{DS(on)}$ VS Drain Current; typical values





Figure 8. Forward characteristics of reverse diode; typical values





Figure 9. Normalized breakdown voltage





Figure 10. Normalized Threshold voltage





Figure 11. Current dissipation





Figure 12. Power dissipation





Figure 13. Maximum Transient Thermal Impedance







Figure 14. Safe Operation Area


## ■ SOT-23 Package information





TOP VIEW




SIDE VIEW




SIDE VIEW




UNIT：mm

SUGGESTED SOLDER PAD LAYOUT

| DIMENSIONS | | | | |
|---|---|---|---|---|
| SYMBOL | INCHES | | Millimeter | |
| | MIN. | MAX. | MIN. | MAX. |
| A | 0.035 | 0.045 | 0.900 | 1.150 |
| A1 | 0.000 | 0.004 | 0.000 | 0.100 |
| A2 | 0.035 | 0.041 | 0.900 | 1.050 |
| b | 0.012 | 0.020 | 0.300 | 0.500 |
| c | 0.004 | 0.008 | 0.100 | 0.200 |
| D | 0.110 | 0.118 | 2.800 | 3.000 |
| E | 0.047 | 0.055 | 1.200 | 1.400 |
| E1 | 0.089 | 0.100 | 2.250 | 2.550 |
| e | 0.037TYP | | 0.950TYP | |
| e1 | 0.071 | 0.079 | 1.800 | 2.000 |
| L | 0.022REF | | 0.550REF | |
| L1 | 0.012 | 0.020 | 0.300 | 0.500 |
| θ | 0° | 8° | 0° | 8° |

NOTE:
1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.

## Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.