
N-Channel Enhancement Mode Field Effect Transistor



Product Summary

- V_{DS} 20 V
- I_D 0.8 A
- $R_{DS(ON)}$(at V_{GS}=4.5V) ＜300 mohm
- $R_{DS(ON)}$(at V_{GS}=2.5V) ＜400 mohm
- $R_{DS(ON)}$(at V_{GS}=1.8V) ＜700 mohm
- ESD Protected Up to 2.0KV (HBM)

General Description

- Trench Power LV MOSFET technology
- High Power and current handing capability
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

Applications

- PWM application
- Load switch

■ Absolute Maximum Ratings (T_A=25℃unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		V_{DS}	20	V
Gate-source Voltage		V_{GS}	±12	V
Drain Current	T_A=25℃ @ Steady State	I_D	0.8	A
	T_A=70℃ @ Steady State		0.6	
Pulsed Drain Current [A]		I_{DM}	3.3	A
Total Power Dissipation @ T_A=25℃		P_D	0.29	W
Thermal Resistance Junction-to-Ambient @ Steady State		$R_{\theta JA}$	420	℃/ W
Junction and Storage Temperature Range		T_J ,T_{STG}	-55～+150	℃

■ Ordering Information

PREFERED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
L3134KADW	F2	34KA	3000	30000	120000	7“ reel

■ Electrical Characteristics (T_J=25℃ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}= 0V, I_D=250μA	20			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=20V,V_{GS}=0V			1	μA
Gate-Body Leakage Current	I_{GSS}	V_{GS}= ±10V, V_{DS}=0V		2.5	±10	μA
		V_{GS}= ±8V, V_{DS}=0V		500	±2000	nA
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}= V_{GS}, I_D=250μA	0.35	0.75	1.1	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	V_{GS}= 4.5V, I_D=0.5A		220	300	mΩ
		V_{GS}= 2.5V, I_D=0.45A		290	400	
		V_{GS}= 1.8V, I_D=0.2A		420	700	
Diode Forward Voltage [C]	V_{SD}	I_S=0.5A,V_{GS}=0V		0.85	1.2	V
Maximum Body-Diode Continuous Current	I_S				0. 5	A
Gate Resistance	Rg	f=1 MHz		50		Ω
Dynamic Parameters [B]						
Input Capacitance	C_{iss}	V_{DS}=10V,V_{GS}=0V,f=1MHZ		33		pF
Output Capacitance	C_{oss}			20		
Reverse Transfer Capacitance	C_{rss}			10		
Switching Parameters [B]						
Total Gate Charge	Q_g	V_{GS}=4.5V,V_{DS}=10V,I_D=0.5A		0.8		nC
Gate Source Charge	Q_{gs}			0.3		
Gate Drain Charge	Q_{gd}			0.15		
Reverse Recovery Chrage	Q_{rr}	I_F=0.5A, di/dt=20A/us		0.4		
Reverse Recovery Time	t_{rr}			14.4		ns
Turn-on Delay Time	$t_{D(on)}$	V_{GS}=4.5V,V_{DD}=10V,R_G=10Ω,I_D=500mA		4		
Turn-on Rise Time	t_r			18.8		
Turn-off Delay Time	$t_{D(off)}$			10		
Turn-off Fall Time	t_f			23		

A. Repetitive Rating: Pulse width limited by maximum junction temperature.
B. These parameters have no way to verify.
C. Pulse Test: Pulse Width≤300us, Duty Cycle≤0.5%.

■ Typical Performance Characteristics




Figure1. Output Characteristics




Figure2. Transfer Characteristics




Figure3. Capacitance Characteristics




Figure4. Gate Charge




Figure5. Drain-Source on Resistance




Figure6. Drain-Source on Resistance




Figure7. Safe Operation Area






Figure8. Switching wave


■SOT-363 Package information




TOP VIEW



SIDE VIEW



SIDE VIEW



UNIT：mm

SUGGESTED SOLDER PAD LAYOUT

DIMENSIONS				
SYMBOL	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.043	0.900	1.100
A1	0.000	0.004	0.000	0.100
A2	0.035	0.039	0.900	1.000
b	0.006	0.014	0.150	0.350
c	0.004	0.010	0.100	0.250
D	0.071	0.087	1.800	2.200
E	0.045	0.053	1.150	1.350
E1	0.085	0.096	2.150	2.450
e	0.026TYP		0.650TYP	
e1	0.047	0.055	1.200	1.400
L	0.021REF		0.525REF	
L1	0.010	0.018	0.260	0.460
θ	0°	8°	0°	8°

NOTE:
1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.