
N-Channel Enhancement Mode Field Effect Transistor




Top View



Bottom View

TO-220



Product Summary

- V_{DS} 100V
- I_D 70A
- $R_{DS(ON)}$(at V_{GS}=10V) ＜8.6 mohm
- $R_{DS(ON)}$(at V_{GS}=4.5V) ＜11 mohm
- 100% EAS Tested
- 100% ▽VDS Tested

General Description

- Low $R_{DS(on)}$ & FOM
- Extremely low switching loss
- Excellent stability and uniformity
- Fast switching and soft recovery
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

Applications

- Power switching application
- Hard switched and high frequency circuits
- Uninterruptible power supply

■ Absolute Maximum Ratings (T_A=25℃unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		V_{DS}	100	V
Gate-source Voltage		V_{GS}	±20	V
Drain Current	T_C=25℃	I_D	70	A
	T_C=100℃		44.2	
Pulsed Drain Current [A]		I_{DM}	280	A
Avalanche energy [B]		EAS	200	mJ
Total Power Dissipation [C]	Tc=25℃	P_D	125	W
	Tc=100℃		50	
Junction and Storage Temperature Range		T_J ,T_{STG}	-55～+150	℃

■Thermal resistance

Parameter		Symbol	Typ	Max	Units
Thermal Resistance Junction-to-Ambient [D]	t≤10S	$R_{\theta JA}$	12	15	℃/W
Thermal Resistance Junction-to-Ambient [D]	Steady-State		50	60	
Thermal Resistance Junction-to-Case	Steady-State	$R_{\theta JC}$	0.8	1.0	

■ Ordering Information (Example)

PREFERED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
P70G10A	B1	P70G10A	50	/	5000	Tube

■ Electrical Characteristics (T_j=25℃ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}= 0V, I_D=250μA	100			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=100,V_{GS}=0V			1	μA
Gate-Body Leakage Current	I_{GSS}	V_{GS}= ±20V, V_{DS}=0V			±100	nA
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}= V_{GS}, I_D=250μA	1	1.8	3	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	V_{GS}= 10V, I_D=20A		7.2	8.6	mΩ
		V_{GS}= 4.5V, I_D=20A		8.8	11	mΩ
Diode Forward Voltage	V_{SD}	I_S=20A,V_{GS}=0V			1.3	V
Maximum Body-Diode Continuous Current	I_S				70	A
Gate resistance	R_G	f= 1 MHz		0.68		Ω
Dynamic Parameters						
Input Capacitance	C_{iss}	V_{DS}=50V,V_{GS}=0V,f=1MHz		2270		pF
Output Capacitance	C_{oss}			797		
Reverse Transfer Capacitance	C_{rss}			36		
Switching Parameters						
Total Gate Charge	Q_g	V_{GS}=10V,V_{DS}=50V,I_D=25A		32		nC
Gate-Source Charge	Q_{gs}			11.1		
Gate-Drain Charge	Q_{gd}			4.78		
Reverse Recovery Chrage	Q_{rr}	I_F=20A, di/dt=100A/us		84		
Reverse Recovery Time	t_{rr}			51.5		ns
Turn-on Delay Time	$t_{D(on)}$	V_{GS}=10V, V_{DD}=50V,I_D=25A R_{GEN}=2.2Ω		51		
Turn-on Rise Time	t_r			14.4		
Turn-off Delay Time	$t_{D(off)}$			69.2		
Turn-off fall Time	t_f			20.6		

A. Repetitive rating; pulse width limited by max. junction temperature.
B. V_{DD}=50V, R_G=25Ω, L=2mH,I_{AS}=14.2A
C. Pd is based on max. junction temperature, using junction-case thermal resistance.
D. The value of $R_{\theta JA}$ is measured with the device mounted on 1in2 FR-4 board with 2oz. Copper, in a still air environment with T_A =25°C. The Power dissipation P_{DSM} is based on $R_{\theta JA}$ t≤ 10s and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.

■ Typical Performance Characteristics




Figure1. Output Characteristics




Figure2. Transfer Characteristics




Figure3. Capacitance Characteristics




Figure4. Gate Charge




Figure5. On-Resistance vs. Drain Current and Gate Voltage




Figure6. Normalized On-Resistance




Figure7. Drain current




Figure8. Safe Operation Area





Figure9. Normalized Maximum Transient thermal impedance

■ TO-220AB-C Package information



DIMENSIONS				
SYMBOL	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A1	0.091	0.098	2.300	2.500
A2	0.173	0.181	4.400	4.600
b	0.028	0.035	0.700	0.900
b2	0.049	0.056	1.250	1.420
c	0.018	0.022	0.450	0.550
c2	0.049	0.053	1.250	1.350
D	0.382	0.402	9.700	10.200
D1	0.295	0.331	7.500	8.400
D2	0.335	0.350	8.500	8.900
E	0.602	0.634	15.300	16.100
E1	0.358	0.366	9.100	9.300
E2	0.497	0.525	12.630	13.330
E3	0.108BSC		2.750BSC	
e	0.200BSC		5.080BSC	
e1	0.100BSC		2.540BSC	
L	0.512	0.531	13.000	13.500
L1	---	0.138	---	3.500
ø	0.140	0.148	3.550	3.750

NOTE:
1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability,or infringement of any patent, copyright, or other intellectual property right.