

N-Channel Enhancement Mode Field Effect Transistor



SOP-8



Product Summary

- V_{DS} 60V
- I_D 12A
- $R_{DS(ON)}$(at V_{GS}=10V) ＜8.5 mohm
- $R_{DS(ON)}$(at V_{GS}=4.5V) ＜12 mohm
- 100% EAS Tested

General Description

- Split Gate Trench MOSFET technology
- Excellent package for heat dissipation
- High density cell design for low $R_{DS(ON)}$
- Moisture Sensitivity Level 3
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

Applications

- DC-DC Converters
- Power management functions
- Industrial and Motor Drive application

■ Absolute Maximum Ratings (T_A=25℃unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		V_{DS}	60	V
Gate-source Voltage		V_{GS}	±20	V
Drain Current (Silicon limited)	T_A=25℃	I_D	12	A
	T_A=100℃		7.5	
Pulsed Drain Current [A]		I_{DM}	48	A
Avalanche energy [B]		E_{AS}	132	mJ
Total Power Dissipation [C]		P_D	3.1	W
Junction and Storage Temperature Range		T_J ,T_{STG}	-55～+150	℃

■Thermal resistance

Parameter		Symbol	Typ	Max	Units
Thermal Resistance Junction-to-Ambient [D]	t≤10S	$R_{\theta JA}$	31	40	℃/W
Thermal Resistance Junction-to-Ambient [D]	Steady-State		59	75	
Thermal Resistance Junction-to-Case	Steady-State	$R_{\theta JL}$	16	24	

■ Ordering Information (Example)

PREFERED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
S12G06D	F2	Q12G06D	4000	8000	64000	13“ reel

■ Electrical Characteristics (T_J=25℃ unless otherwise noted)

Parameter	Symbol	Conditions		Min	Typ	Max	Units
Static Parameter							
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}= 0V, I_D=250μA		60			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=60V,V_{GS}=0V	T_J=25℃			1	μA
			T_J=55℃			5	
Gate-Body Leakage Current	I_{GSS}	V_{GS}= ±20V, V_{DS}=0V				±100	nA
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}= V_{GS}, I_D=250μA		1.2	1.7	2.5	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	V_{GS}= 10V, I_D=12A			6.8	8.5	mΩ
		V_{GS}= 4.5V, I_D=10A			8.3	12	
Diode Forward Voltage	V_{SD}	I_S=12A,V_{GS}=0V			0.85	1.3	V
Maximum Body-Diode Continuous Current	I_S					12	A
Dynamic Parameters							
Input Capacitance	C_{iss}	V_{DS}=35V,V_{GS}=0V,f=1MHZ			2000		pF
Output Capacitance	C_{oss}				390		
Reverse Transfer Capacitance	C_{rss}				13		
Gate Resistance	R_g	f=1MHZ, Open drain			1.6		Ω
Switching Parameters							
Total Gate Charge	Q_g(10V)	V_{DS}=30V,I_D=12A			34		nC
Total Gate Charge	Q_g(4.5V)				15.8		
Gate-Source Charge	Q_{gs}				7.8		
Gate-Drain Charge	Q_{gd}				5.2		
Reverse Recovery Charge	Q_{rr}	I_F=12A, di/dt=200A/us			36		
Reverse Recovery Time	t_{rr}				27		ns
Turn-on Delay Time	$t_{D(on)}$	V_{GS}=10V,V_{DD}=30V,I_D=12A R_{GEN}=3Ω			10		
Turn-on Rise Time	t_r				36		
Turn-off Delay Time	$t_{D(off)}$				30		
Turn-off fall Time	t_f				57		

A. Repetitive rating; pulse width limited by max. junction temperature.
B. V_{DD}=50V, R_G=25Ω, L=0.5mH, I_{AS}=23A,.
C. Pd is based on max. junction temperature, using ≤10s junction-ambient thermal resistance.
D. The value of RθJA is measured with the device mounted on 1in2 FR-4 board with 2oz. Copper, in a still air environment with TA =25° C. The Power dissipation PDSM is based on RθJA t≤ 10s and the maximum allowed junction temperature of 150° C. The value in any given application depends on the user's specific board design.

■ Typical Performance Characteristics




Figure1. Output Characteristics




Figure2. Transfer Characteristics




Figure3. Capacitance Characteristics




Figure4. Gate Charge




Figure5. Drain-Source on Resistance




Figure6. Normalized On-Resistance




Figure7. Drain current




Figure8. Safe Operation Area




Figure 9. On-Resistance vs Gate to Source Voltage




Figure 10. Forward characteristics of reverse diode




Figure 11. Normalized breakdown voltage




Figure 12. Normalized Threshold voltage






Figure13. Normalized Maximum Transient Thermal Impedance


■ SOP-8 Package information




TOP VIEW



SIDE VIEW



SIDE VIEW



Suggested Solder Pad Layout

DIMENSIONS				
SYMBOL	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.053	0.069	1.350	1.750
B	0.004	0.010	0.100	0.250
C	0.053	0.061	1.350	1.550
D	0.013	0.020	0.330	0.510
E	0.007	0.010	0.170	0.250
F	0.189	0.197	4.800	5.000
G	0.050BSC		1.270BSC	
H	0.228	0.244	5.800	6.200
J	0.150	0.157	3.800	4.000
K	0.016	0.050	0.400	1.270
θ	0°	8°	0°	8°

Note:
1.Controlling dimension:in millimeters.
2.General tolerance:+/-0.05mm.
3.The pad layout is for reference purposes only.

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.