

# N-Channel Enhancement Mode Field Effect Transistor




SOP-8




## Product Summary

- $V_{DS}$ 100 V
- $I_D$ 12A
- $R_{DS(ON)}$( at $V_{GS}$=10V) < 19mΩ
- $R_{DS(ON)}$( at $V_{GS}$=4.5V) < 24mΩ

## General Description

- Split gate trench MOSFET technology
- Low $R_{DS(on)}$ & FOM
- Extremely low switching loss
- Excellent stability and uniformity
- Moisture Sensitivity Level 3
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free

## Applications

- Power management
- Portable equipment

## ■ Absolute Maximum Ratings ($T_A$=25℃ unless otherwise noted)

| Parameter | | Symbol | Limit | Unit |
|---|---|---|---|---|
| Drain-source Voltage | | $V_{DS}$ | 100 | V |
| Gate-source Voltage | | $V_{GS}$ | ±20 | V |
| Drain Current | $T_A$=25℃ | $I_D$ | 12 | A |
| | $T_A$=100℃ | | 7.6 | |
| Pulsed Drain Current [A] | | $I_{DM}$ | 50 | A |
| Total Power Dissipation [B] | $T_A$=25℃ | $P_D$ | 4.1 | W |
| | $T_A$=100℃ | | 1.6 | |
| Junction and Storage Temperature Range | | $T_J$ ,$T_{STG}$ | -55～+150 | ℃ |

## ■Thermal resistance

| Parameter | | Symbol | Typ | Max | Units |
|---|---|---|---|---|---|
| Thermal Resistance Junction-to-Ambient [C] | Steady-State | $R_{\theta JA}$ | 25 | 30 | ℃/W |

## ■ Ordering Information (Example)

| PREFERED P/N | PACKING CODE | Marking | MINIMUM PACKAGE(pcs) | INNER BOX QUANTITY(pcs) | OUTER CARTON QUANTITY(pcs) | DELIVERY MODE |
|---|---|---|---|---|---|---|
| S12G10B | F2 | Q12G10B | 4000 | 8000 | 64000 | 13“ reel |

## ■ Electrical Characteristics ($T_J$=25℃ unless otherwise noted)

| Parameter | Symbol | Conditions | Min | Typ | Max | Units |
|---|---|---|---|---|---|---|
| **Static Parameter** | | | | | | |
| Drain-Source Breakdown Voltage | $BV_{DSS}$ | $V_{GS}$= 0V, $I_D$=250μA | 100 | - | - | V |
| Zero Gate Voltage Drain Current | $I_{DSS}$ | $V_{DS}$=100V, $V_{GS}$=0V | - | - | 1 | μA |
| | | $V_{DS}$=100V, $V_{GS}$=0V, Tj=150℃ | - | - | 100 | |
| Gate-Body Leakage Current | $I_{GSS}$ | $V_{GS}$= ±20V, $V_{DS}$=0V | - | - | ±100 | nA |
| Gate Threshold Voltage | $V_{GS(th)}$ | $V_{DS}$= $V_{GS}$, $I_D$=250μA | 1.2 | 1.9 | 2.8 | V |
| Static Drain-Source On-Resistance | $R_{DS(on)}$ | $V_{GS}$=10V, $I_D$=12A | - | 14.5 | 19 | mΩ |
| | | $V_{GS}$=4.5V, $I_D$=10A | - | 18 | 24 | |
| Diode Forward Voltage | $V_{SD}$ | $I_S$=12A, $V_{GS}$=0V | - | 0.9 | 1.2 | V |
| Gate resistance | $R_G$ | f=1MHz, Open drain | - | 1.3 | - | Ω |
| Maximum Body-Diode Continuous Current | $I_S$ | | - | - | 12 | A |
| **Dynamic Parameters** | | | | | | |
| Input Capacitance | $C_{iss}$ | $V_{DS}$=50V, $V_{GS}$=0V, f=1MHz | - | 1150 | - | pF |
| Output Capacitance | $C_{oss}$ | | - | 380 | - | |
| Reverse Transfer Capacitance | $C_{rss}$ | | - | 8.5 | - | |
| **Switching Parameters** | | | | | | |
| Total Gate Charge | $Q_g$ | $V_{GS}$=10V, $V_{DS}$=50V, $I_D$=10A | - | 32 | - | nC |
| Gate-Source Charge | $Q_{gs}$ | | - | 11 | - | |
| Gate-Drain Charge | $Q_{gd}$ | | - | 5 | - | |
| Reverse Recovery Charge | $Q_{rr}$ | $I_F$=10A, di/dt=100A/us | - | 84 | - | nC |
| Reverse Recovery Time | $t_{rr}$ | | - | 51.5 | - | ns |
| Turn-on Delay Time | $t_{D(on)}$ | $V_{GS}$=10V, $V_{DD}$=50V, $I_D$=10A $R_{GEN}$=2.2Ω | - | 51 | - | ns |
| Turn-on Rise Time | $t_r$ | | - | 14.4 | - | |
| Turn-off Delay Time | $t_{D(off)}$ | | - | 69.2 | - | |
| Turn-off fall Time | $t_f$ | | - | 20.6 | - | |

A. Repetitive rating; pulse width limited by max. junction temperature.
B. $P_d$ is based on max. junction temperature, using junction-case and junction-ambient thermal resistance.
C. The value of $R_{\theta JA}$ is measured with the device mounted on 1 $in^2$ FR-4 board with 2oz. Copper, in the still air environment with $T_A$ =25℃. The maximum allowed junction temperature of 150℃. The value in any given application depends on the user's specific board design.

## ■Typical Electrical and Thermal Characteristics Diagrams





Figure 1. Output Characteristics





Figure 2. Transfer Characteristics





Figure 3. Capacitance Characteristics





Figure 4. Gate Charge





Figure 5. On-Resistance vs Gate to Source Voltage





Figure 6. Normalized On-Resistance





Figure 7. $R_{DS(on)}$ VS Drain Current





Figure 8. Forward characteristics of reverse diode





Figure 9. Normalized breakdown voltage





Figure 10. Normalized Threshold voltage





Figure 11. Current dissipation





Figure 12. Power dissipation





Figure 13. Maximum Transient Thermal Impedance








Figure 14. Safe Operation Area

## ■ SOP8 Package information




| DIMENSIONS | | | | |
|---|---|---|---|---|
| SYMBOL | INCHES | | Millimeter | |
| | MIN. | MAX. | MIN. | MAX. |
| A | 0.053 | 0.069 | 1.350 | 1.750 |
| B | 0.004 | 0.010 | 0.100 | 0.250 |
| C | 0.053 | 0.061 | 1.350 | 1.550 |
| D | 0.013 | 0.020 | 0.330 | 0.510 |
| E | 0.007 | 0.010 | 0.170 | 0.250 |
| F | 0.189 | 0.197 | 4.800 | 5.000 |
| G | 0.050BSC | | 1.270BSC | |
| H | 0.228 | 0.244 | 5.800 | 6.200 |
| J | 0.150 | 0.157 | 3.800 | 4.000 |
| K | 0.016 | 0.050 | 0.400 | 1.270 |
| θ | 0° | 8° | 0° | 8° |

Note:
1.Controlling dimension:in millimeters.
2.General tolerance:+/-0.05mm.
3.The pad layout is for reference purposes only.

## Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.