
# Silicon Carbide Schottky Diode

| | |
|---|---|
| $V_{RRM}$ | 1200V |
| $I_{F(135°C)}$ | 24A |
| $Q_C$ | 100nC |




## Features

- Positive temperature coefficient
- Temperature-independent switching
- Maximum working temperature at 175 °C
- Unipolar devices and zero reverse recovery current
- Zero forward recovery current
- Essentially no switching losses
- Reduction of heat sink requirements
- High-frequency operation
- Reduction of EMI

## Typical Applications

Typical applications are in power factor correction(PFC), solar inverter, uninterruptible power supply, motor drives, photovoltaic inverter, electric car and charger.

## Mechanical Data

- **Package**: TO-247AC
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals**: Tin plated leads
- **Polarity**: As marked

## ■Maximum Ratings ($T_C$=25°C Unless otherwise specified)

| PARAMETER | SYMBOL | UNIT | VALUE |
|---|---|---|---|
| Device marking code | | | D112020NYG6 |
| Reverse voltage (Repetitive peak) @ $T_j$=25°C | $V_{RRM}$ | V | 1200 |
| Reverse voltage (Surge peak) @ $T_j$=25°C | $V_{RSM}$ | V | 1200 |
| Reverse voltage (DC) @ $T_j$=25°C | $V_{DC}$ | V | 1200 |
| Continuous forward current @ $T_C$=25°C | $I_F$ | A | 52 |
| Continuous forward current @ $T_C$=135°C | | | 24 |
| Continuous forward current @ $T_C$=146°C | | | 20 |
| Non-repetitive peak forward surge current @ $T_C$=25°C, tp=10ms, Half Sine Wave | $I_{FSM}$ | A | 200 |
| Repetitive peak forward surge current @ $T_C$=25°C, tp=10ms, Half Sine Wave，D=0.1 | $I_{FRM}$ | A | 120 |
| Power Dissipation@ $T_C$=25°C | $P_{TOT}$ | W | 205 |
| Power Dissipation@ $T_C$=110°C | | | 89 |
| $i^2t$ Value@ $T_C$=25°C ,tp=10ms | $\int i^2dt$ | $A^2S$ | 200 |
| Operating junction and Storage temperature range | $T_j$ ,$T_{stg}$ | °C | -55 to +175 |

## ■Electrical Characteristics ($T_C$=25°C Unless otherwise specified)

| PARAMETER | SYMBOL | UNIT | TEST CONDITIONS | Min. | Typ. | Max. |
|---|---|---|---|---|---|---|
| Reverse voltage (DC) | $V_{DC}$ | V | $I_R$=0.25mA, $T_j$=25°C | 1200 | - | - |
| Forward voltage | $V_F$ | V | $I_F$=20A, $T_j$=25°C | - | 1.38 | 1.60 |
| | | | $I_F$=20A, $T_j$=175°C | - | 1.93 | - |
| Reverse current | $I_R$ | μA | $V_R$=1200V, $T_j$=25°C | - | 3 | 25 |
| | | | $V_R$=1200V, $T_j$=175°C | - | 60 | - |
| Total capacitive charge | $Q_C$ | nC | $V_R$=800V, $T_j$=25°C , $Q_C=\int_0^{VR} C(V)dV$ | - | 100 | - |
| Total capacitance | C | pF | $V_R$=0V, f=1MHZ | - | 1388 | - |
| | | | $V_R$=400V, f=1MHZ | - | 93 | - |
| | | | $V_R$=800V, f=1MHZ | - | 74 | - |
| Capacitance stored energy | $E_C$ | μJ | $V_R$=800V | - | 29 | - |

## ■Thermal Characteristics

| PARAMETER | SYMBOL | UNIT | VALUE |
|---|---|---|---|
| Thermal resistance | $R_{\theta J-C}$ | °C /W | 0.73 |

## ■Typical Characteristics (Typical)





Figure 1. Forward Characteristics





Figure 2. Reverse Characteristics





Figure 3. Capacitance vs. Reverse Voltage





Figure 4. Total Capacitance Charge vs. Reverse Voltage





Figure 5. Capacitance Stored Energy





Figure 6. Power Derating





Figure 7. Current Derating






Figure 8. Transient Thermal Impedance

## ■Outline Dimensions

**TO-247AC**




| TO-247AC | | |
|---|---|---|
| Dim | Min | Max |
| A | 4.80 | 5.20 |
| A1 | 2.21 | 2.61 |
| A2 | 1.85 | 2.15 |
| b | 1.11 | 1.36 |
| b2 | 1.91 | 2.21 |
| c | 0.51 | 0.75 |
| D | 20.70 | 21.30 |
| D1 | 16.25 | 16.85 |
| E | 15.50 | 16.10 |
| E1 | 13.00 | 13.60 |
| E2 | 4.80 | 5.20 |
| E3 | 2.30 | 2.70 |
| e | 10.88BSC | |
| L | 19.62 | 20.22 |
| L1 | - | 4.30 |
| ΦP | 3.40 | 3.80 |
| ΦP1 | - | 7.30 |
| S | 6.15BSC | |

## Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.