
Silicon Carbide Schottky Diode

V_{RRM}	1200V
$I_{F\ (135°C)}$	70A[2]
Q_C	360nC[2]



Features

- Positive temperature coefficient
- Temperature-independent switching
- Maximum working temperature at 175 °C
- Unipolar devices and zero reverse recovery current
- Zero forward recovery current
- Essentially no switching losses
- Reduction of heat sink requirements
- High-frequency operation
- Reduction of EMI

Typical Applications

Typical applications are in power factor correction(PFC), solar inverter, uninterruptible power supply, motor drives, photovoltaic inverter, electric car and charger.

Mechanical Data

- **Package**: TO-247AB
- **Terminals**: Tin plated leads
- **Polarity**: As marked

■Maximum Ratings (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	VALUE
Device marking code			D112060NCTYG5
Reverse voltage (Repetitive peak) @ T_j=25°C	V_{RRM}	V	1200
Reverse voltage (Surge peak) @ T_j=25°C	V_{RSM}	V	1200
Reverse voltage (DC) @ T_j=25°C	V_{DC}	V	1200
Continuous forward current @ T_C=25°C	I_F	A	76/152
Continuous forward current @ T_C=135°C			35/70
Continuous forward current @ T_C=144°C			30/60
Non-repetitive peak forward surge current @ T_C=25°C, tp=10ms, Half Sine Wave	I_{FSM}	A	320[1]
Power Dissipation@ T_C=25°C	P_{TOT}	W	277/535
Power Dissipation@ T_C=110°C			120/232
i^2t Value@ T_C=25°C ,tp=10ms	$\int i^2dt$	A^2S	512[1]
Operating junction and Storage temperature range	T_j ,T_{stg}	°C	-55 to +175

[1] Per Leg, [2] Per Device

■Electrical Characteristics (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Typ.	Max.
Forward voltage drop	V_F	V	I_F=30A, T_j=25°C	1.35	1.60
			I_F=30A, T_j=175°C	1.90	-
Reverse current	I_R	μA	V_R=1200V, T_j=25°C	1	25
			V_R=1200V, T_j=175°C	50	-
Total capacitive charge	Q_C	nC	V_R=800V, T_j=25°C , $Q_C=\int_0^{VR} C(V)dV$	180	-
Total capacitance	C	pF	V_R=0V, f=1MHZ	2460	-
			V_R=400V, f=1MHZ	169	-
			V_R=800V, f=1MHZ	128	-
Capacitance stored energy	E_C	μJ	V_R=800V	51	-

■Thermal Characteristics (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	VALUE
Thermal resistance	$R_{\theta J-C}$	°C /W	0.54(1) 0.28(2)

(1) Per Leg, (2) Per Device

■Typical Characteristics (Typical)




Figure 1. Forward Characteristics




Figure 2. Reverse Characteristics




Figure 3. Capacitance vs. Reverse Voltage




Figure 4. Total Capacitance Charge vs. Reverse Voltage




Figure 5. Capacitance Stored Energy




Figure 6. Power Derating




Figure 7. Current Derating

■Typical Characteristics (Device)





Figure 8. Transient Thermal Impedance

■Outline Dimensions



TO-247AB		
Dim	Min	Max
A	4.80	5.20
A1	2.21	2.61
A2	1.85	2.15
b	1.0	1.4
b2	1.91	2.21
C	0.5	0.7
D	20.70	21.30
D1	16.25	16.85
E	15.50	16.10
E1	13.0	13.6
E2	4.80	5.20
E3	2.30	2.70
L	19.62	20.22
L1	-	4.30
ΦP	3.40	3.80
ΦP1	-	7.30
S	6.15TYP	
H1	5.44TYP	
b3	2.80	3.20

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.