
SiC Diode Power Module



V_{DC}	1700V
I_F	2×40A
$T_{J,max}$	175°C

Circuit



Applications

- Welding equipment
- Uninterruptible power supply (UPS)
- High frequency power supply
- Induction heating
- High speed rectifiers

Features

- SiC Schottky Diode
  - Zero reverse recovery
  - Zero forward recovery
  - Temperature independent switching behavior
  - Positive temperature coefficient on V_F
- Very low stray inductance
- Low forward voltage
- Isolated package (SOT-227)
- Low noise switching
- RoHS compliant

■ Absolute Maximum Ratings (T_J=25°C unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	VALUE	UNIT
Peak Repetitive Reverse Voltage	V_{RRM}	T_J=25°C	1700	V
DC Blocking Voltage	V_{DC}	T_J=25°C	1700	V
Continuous Forward Current	I_F	T_C=25°C, T_J=175°C	86	A
		T_C=135°C, T_J=175°C	40	
		T_C=145°C, T_J=175°C	33	
Non-Repetitive Peak Forward Surge Current	I_{FSM}	T_C=25°C, T_P=10ms, Half Sine Wave	515	A
I^2t Value	$\int I^2dt$	T_C=25°C, T_P=10ms	1325	A^2s
Power Dissipation	P_{Tot}	T_C=25°C	310	W
Operating Junction Temperature	$T_{J,op}$		-55…175	°C
Storage Temperature	T_{STG}		-55…175	°C

■ Electrical Characteristics (T_J=25°C unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	VALUE			UNIT
			Min.	Typ.	Max.	
Reverse Current	I_R	V_R=1700V, T_J=25°C	--	3.2	30	μA
		V_R=1700V, T_J=175°C	--	17.2	--	
Forward Voltage	V_F	I_F=40A, T_J=25°C	--	1.42	1.71	V
		I_F=40A, T_J=175°C	--	2.10	--	
Total Capacitance	C	V_R=1V, f=1MHz	--	3037	--	pF
		V_R=800V, f=1MHz	--	190	--	
		V_R=1700V, f=1MHz	--	165	--	
Total Capacitive Charge	Q_C	V_R=1700V	--	430	--	nC
Capacitance Stored Energy	E_C	V_R=1700V	--	233	--	μJ

■ Thermal and Package Characteristics (T_J=25°C unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	VALUE			UNIT
			Min.	Typ.	Max.	
Thermal Resistance, Junction to Case	R_{thJC}	Per leg		0.48		°C/W
Isolation Breakdown Voltage	V_{isol}	AC, 50Hz (R.M.S), t=1min		3000		V
Mounting Torque	M	Recommended (M4 screw)	1.1		1.5	Nm
Terminal Connection Torque		Recommended (M4 screw)	1.1		1.5	
Weight	W			25		g

■ Typical Performance Per Leg

Fig1. Forward Characteristics




Fig2. Reverse Characteristics




Fig3. Current Derating




Fig4. Power Derating




Fig5. Recovery Charge vs. Reverse Voltage




Fig6. Capacitance vs. Reverse Voltage




Fig7. Typical Capacitance Stored Energy







Fig8. Transient Thermal Impedance



■ Package Outline Information

CASE: ST





DIM	Millimeter	
	min	max
A	31.40	31.60
B	7.70	8.10
C	4.20	4.40
D	4.20	4.40
E	4.10	4.30
F	14.90	15.10
G	30.10	30.40
H*	38.00	38.40
I	23.80	24.20
J*	12.20	12.70
K*	9.40	9.60
L	0.75	0.85
M	12.40	12.80
N*	24.50	25.40
O*	1.90	2.10
P	3.10	3.95
Q*	26.60	27.00
R*	3.80	4.20
S	5.10	5.40
Marked * is primary/accent size		

Disclaimer

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.
Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.