
2- Line, Uni-directional, Transient Voltage Suppressor



Features


- Transient protection for each line according to IEC61000-4-2(ESD): ±30kV contact, ±30kV air IEC61000-4-5: 30A (tp=8/20μs)
- Low leakage current
- Ultra low clamping voltage
- RoHS Compliant

Applications


- Peripherals
- Industrial Equipment
- Notebook Computers
- Portable Instrumentation
- Microprocessor Based Equipment
- Cell Phone Handsets and Accessories
- Personal Digital Assistants (PDAs) and Pagers

Mechanical Data

- Package: SOT-23
- Lead Finish: Matte Tin
- Case Material: “Green” Molding Compound
- Moisture Sensitivity: Level 1 per J-STD-020



■Definitions of electrical characteristics



■Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power (t_p = 8/20μs)	P_{pk}	510	W
Peak pulse current (t_p = 8/20μs)	I_{PP}	30	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	±30	KV
ESD according to IEC61000-4-2 contact discharge		±30	
Junction temperature	T_J	-55~150	℃
Storage temperature	T_{STG}	-55~150	℃

Notes:

CAUTION: Stresses above those listed in “Absolute Maximum Ratings” may cause permanent damage to the component. This is a stress only rating and operation of the component at these or any other conditions above those indicated in the operational sections of this specification is not implied.

■Electrical Characteristics（T_J=25℃）

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse Standoff Voltage	V_{RWM}	V				8
Reverse leakage current	I_R	μA	V_{RWM} = 8V			10
Reverse breakdown voltage	V_{BR}	V	I_T = 1mA	8.5		
Forward Voltage	V_F	V	I_F=10mA			1.25
Clamping voltage 1)	V_C	V	I_{PP} = 1A, t_p = 8/20μs		9.8	10
			I_{PP} = 30A, t_p = 8/20μs		15	17
Junction capacitance	C_J	pF	V_R = 0V, f = 1MHz		200	

Notes:

(1). Non-repetitive current pulse, according to IEC61000-4-5.

(2). TLP parameter: Z_0 = 50Ω, t_p = 100ns, t_r = 2ns, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ESD0812E	F2	Approximate 10	3000	30000	120000	7 reel

Characteristics (Typical)

Fig.1 8/20us Waveform Per iec6100-4-5




Fig.2 Contact Discharge Current Waveform per IEC61000-4-2




Fig.3 ClampingVoltage VS Peak Pulse Current




Fig.4 Capacitance vs. Reverse voltage




Fig.5 Non-repetitive peak pulse power vs. Pulse time







Fig.6 Power Derating Curve




■ Outline Dimensions




TOP VIEW



SIDE VIEW



SIDE VIEW



UNIT: mm

SUGGESTED SOLDER PAD LAYOUT

DIMENSIONS				
SYMBOL	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.045	0.900	1.150
A1	0.000	0.004	0.000	0.100
A2	0.035	0.041	0.900	1.050
b	0.012	0.020	0.300	0.500
c	0.004	0.008	0.100	0.200
D	0.110	0.118	2.800	3.000
E	0.047	0.055	1.200	1.400
E1	0.089	0.100	2.250	2.550
e	0.037TYP		0.950TYP	
e1	0.071	0.079	1.800	2.000
L	0.022REF		0.550REF	
L1	0.012	0.020	0.300	0.500
θ	0°	8°	0°	8°

NOTE:
1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.