
2-Line, Bi-directional, Transient Voltage Suppressor



Features


- Transient protection for each line according to
  IEC61000-4-2(ESD): ±30kV contact, ±30kV air
  IEC61000-4-5:9A(tp=8/20μs)
- Low leakage current
- Ultra low clamping voltage
- RoHS Compliant

Applications


- Cellular Handsets and Accessories
- Notebooks and Handhelds
- Portable Instrumentation
- Set Top Box
- Industrial Controls
- Server and Desktop PC

Mechanical Data

- Package: SOT-23
- Lead Finish: Matte Tin
- Case Material: “Green” Molding Compound
- Moisture Sensitivity: Level 1 per J-STD-020
- Marking Information: See Below



■Definitions of electrical characteristics



■Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power (t_p = 8/20μs)	P_{pk}	270	W
Peak pulse current (t_p = 8/20μs)	I_{PP}	9	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	±30	KV
ESD according to IEC61000-4-2 contact discharge		±30	
Junction temperature	T_J	-55~150	℃
Storage temperature	T_{STG}	-55~150	℃

Notes:

CAUTION: Stresses above those listed in “Absolute Maximum Ratings” may cause permanent damage to the component. This is a stress only rating and operation of the component at these or any other conditions above those indicated in the operational sections of this specification is not implied.

■Electrical Characteristics（T_J=25℃）

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V				15
Reverse leakage current	I_R	μA	V_{RWM} = 15V			0.5
Reverse breakdown voltage	V_{BR}	V	I_T = 1mA	15.5		18
Clamping voltage [1)]	V_{CL}	V	I_{PP} = 16A, t_p = 0.2/100ns(TLP)		24	
Dynamic resistance [2)]	R_{DYN}	Ω	TLP, tp=100ns, I/O to Ground		0.39	
Clamping voltage [1)]	V_C	V	I_{PP} = 1A, t_p = 8/20μs			21
		V	I_{PP} = 5A, t_p = 8/20μs			25
		V	I_{PP} = 9A, t_p = 8/20μs			30
Junction capacitance	C_J	pF	V_R = 0V, f = 1MHz		27	46

Notes:

(1). Non-repetitive current pulse, according to IEC61000-4-5.

(2). TLP parameter: Z_0 = 50Ω, t_p = 100ns, t_r = 2ns, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ESD1502EB	F2	Approximate 10	3000	30000	120000	7 reel

■ Characteristics (Typical)

Fig.1 8/20us Waveform Per iec6100-4-5




Fig.2 Contact Discharge Current Waveform per IEC61000-4-2




Fig.3 ClampingVoltage VS Peak Pulse Current




Fig.4 Capacitance VS Bias




Fig.4 Non-Repetitive Peak Pulse Power vs Pulse Time




Fig.5 Power Derating Curve






Fig.6 Trans mission Line Pulsing(TLP)Plot



■ Outline Dimensions



DIMENSIONS				
SYMBOL	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.045	0.900	1.150
A1	0.000	0.004	0.000	0.100
A2	0.035	0.041	0.900	1.050
b	0.012	0.020	0.300	0.500
c	0.004	0.008	0.100	0.200
D	0.110	0.118	2.800	3.000
E	0.047	0.055	1.200	1.400
E1	0.089	0.100	2.250	2.550
e	0.037TYP		0.950TYP	
e1	0.071	0.079	1.800	2.000
L	0.022REF		0.550REF	
L1	0.012	0.020	0.300	0.500
θ	0°	8°	0°	8°

NOTE:
1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.