
1-Line , Uni-directional , Transient Voltage Suppressor



Features


- Ultra small package
- Stand-off voltage: 18V
- Transient protection for each line according to
  IEC61000-4-2(ESD): ±30kV (contact)
  IEC61000-4-4 (EFT): 80A (5/50ns)
  IEC61000-4-5(surge):50A (8/20μs)
- Low clamping voltage
- RoHS Compliant

Applications


- Power supply protection
- Power management
- Battery Contacts

Mechanical Characteristics

- Package: DFN1610-2L
- Case Material: “Green” Molding Compound.
- Moisture Sensitivity: Level 3 per J-STD-020
- Marking Information: See Below



■Definitions of electrical characteristics



■Absolute Maximum Ratings (Ta=25°C unless otherwise specified)

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power (t_p = 8/20μs)	P_{pk}	1800	W
Peak pulse current (t_p = 8/20μs)	I_{PP}	50	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	±30	kV
ESD according to IEC61000-4-2 contact discharge		±30	
Operating Temperature Range	T_J	-55~125	℃
Storage Temperature Range	T_{STG}	-55~150	℃

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V				18
Reverse leakage current	I_R	μA	V_{RWM} = 18V			1
Reverse breakdown voltage	V_{BR}	V	I_{BR} = 1mA	19.2		22.5
Forward voltage	V_F	V	I_F = 20mA	0.45		1.25
Clamping voltage [1)]	V_{CL}	V	I_{PP} = 50A, t_p = 8/20μs			35
Junction capacitance	C_J	pF	V_R = 0V, f = 1MHz		280	310

Notes:
(1). Non-repetitive current pulse, according to IEC61000-4-5. (8/20μs current waveform).

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ESD18VP6A	F1	Approximate 270	3000	30000	120000	7” reel

■Typical Performance Characteristics (T_a=25℃ unless otherwise Specified)

Fig.1 8/20μs waveform per IEC61000-4-5




Fig.2 Contact discharge current waveform per IEC61000-4-2




Fig.3 Clamping voltage vs. Peak pulse current




Fig.4 Non-repetitive peak pulse power vs. Pulse time






Fig.4 Power derating vs. Ambient temperature




■Outline Dimensions



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	0.45	0.50	0.55
A1	0.00	0.02	0.05
c		0.15 Ref.	
b	0.75	0.80	0.85
L	0.35	0.40	0.45
D	1.55	1.60	1.65
E	0.95	1.00	1.05
e		1.10 BSC	
h		0.20 Ref.	

■Recommend land pattern (Unit:mm)



Notes:
This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met.

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.