
1-Line , Uni-directional , Transient Voltage Suppressor



Features


- Ultra small package
- Stand-off voltage: 4.5V ~5V
- Transient protection for each line according to
  IEC61000-4-2(ESD): ±30kV (contact)
  IEC61000-4-4 (EFT): 40A (5/50ns)
  IEC61000-4-5(surge): 7A (8/20μs)
- Low clamping voltage
- RoHS Compliant

Applications


- Power supply protection
- Power management
- Battery Contacts

Mechanical Characteristics

- Package: DFN1610-2L
- Case Material: “Green” Molding Compound.
- Moisture Sensitivity: Level 3 per J-STD-020
- Marking Information: See Below



■Definitions of electrical characteristics



■Absolute Maximum Ratings (Ta=25°C unless otherwise specified)

PARAMETER	SYMBOL		VALUE	UNIT
Peak pulse power (t_p = 8/20μs)	P_{pk}		2400	W
ESD IEC61000-4-2(ESD)Air	V_{ESD}		±30	KV
ESD IEC61000-4-2(ESD)Contact			±30	KV
Operating Temperature Range	T_J		-55~125	℃
Storage Temperature Range	T_{STG}		-55~150	℃

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）


Part Number	Reverse Working Voltage V_{RWM}(V)	Breakdown Voltage V_{BR}(V)@I_T=1mA			Reverse Leakage Current I_R(μA)@V_{RWM}		Forward Voltage V_F(V)@I_F=20mA		Junction Capacitance Cj(pF)@ VR=0V,f=1MHz	
	Max	Min	Typ	Max	Typ	Max	Min	Max	Typ	Max
ESD4V5P6A	4.5	4.9	5.4	6.0	-	1	0.45	1.25	600	700
ESD5V0P6A	5.0	5.2	6.4	7.0	-	1	0.45	1.25	500	600

Part Number	Rated peak pulse current IPP （A） 1)	Clamping voltage VCL(V) @ IPP （A） 1)	
	Max	Typ	Max
ESD4V5P6A	170	12	14
ESD5V0P6A	160	12	14


Notes:
(1). Non-repetitive current pulse, according to IEC61000-4-5. (8/20μs current waveform).

■Typical Performance Characteristics (T_a=25℃ unless otherwise Specified)


8/20μs waveform per IEC61000-4-5




Contact discharge current waveform per IEC61000-4-2




Clamping voltage vs. Peak pulse current




Non-repetitive peak pulse power vs. Pulse time



Power derating vs. Ambient temperature




■Outline Dimensions



SYM	DIMENSIONS					
	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.45	0.50	0.55	0.018	0.020	0.022
A1	0.00	0.02	0.05	0.000	0.001	0.002
b	0.75	0.80	0.85	0.030	0.032	0.034
c	0.10	0.15	0.20	0.004	0.006	0.008
D	1.55	1.60	1.65	0.062	0.064	0.066
e	1.10 BSC			0.044 BSC		
E	0.95	1.00	1.05	0.038	0.040	0.042
L	0.35	0.40	0.45	0.014	0.016	0.018
h	0.15	0.20	0.25	0.006	0.008	0.010

■Recommend land pattern (Unit:mm)



SYM	DIMENSIONS	
	MILLIMETERS	INCHES
X	1.00	0.040
Y1	0.62	0.025
Y2	0.60	0.024
Y3	1.22	0.049
Z	1.85	0.074

Notes:
This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met.

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.