
# ESD Protection Diode




## Features

- For sensitive ESD protection
- Low leakage
- Uni-directional ESD protection of one line
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

## Mechanical Data

- **Package**: SOD323
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end
- **Marking:** ZF


## ■Maximum Ratings

| PARAMETER | SYMBOL | LIMITS | UNIT |
|---|---|---|---|
| Operating Junction & Storage Temperature | $T_J$&$T_{STG}$ | -45 to +125 | ℃ |
| IEC61000-4-2(ESD)Air | $V_{ESD}$ (1) | ±30 | KV |
| IEC61000-4-2(ESD)Contact | | ±30 | KV |
| Peak Pulse Current, $t_P$=8/20μs | $I_{PP}$ (2) | 15 | A |
| Peak Power Dissipation, $t_P$=8/20μs | $P_{PK}$ (2) | 350 | W |

(1).Device stressed with ten non-repetitive ESD pulses.
(2).Non-repetitive current pulse 8/20μs exponential decay waveform according to IEC61000-4-5.

## ■Electrical Parameter

| PARAMETER | SYMBOL |
|---|---|
| Clamping Voltage@ $I_{PP}$ | $V_C$ |
| Breakdown Voltage@ $I_T$ | $V_{BR}$ |
| Peak Pulse Current | $I_{PP}$ |
| Test Current | $I_T$ |
| Reverse Leakage Current@ $V_{RWM}$ | $I_R$ |
| Reverse Standoff Voltage | $V_{RWM}$ |
| Forward Voltage@ $I_F$ | $V_F$ |
| Forward Current | $I_F$ |
| Peak Power Dissipation | $P_{PK}$ |
| Junction Capacitance @ $V_R$=0 and f=1MHz | Cj |



## ■Electrical Characteristics（$T_a$=25℃ Unless otherwise specified）

| PARAMETER | Symbol | UNIT | Conditions | Min | Typ | Max |
|---|---|---|---|---|---|---|
| Reverse Standoff Voltage | $V_{RWM}$ (1) | V | | | | 5.0 |
| Reverse Leakage Current | $I_R$ | μA | $V_{RWM}$=5.0V | | | 1 |
| Breakdown Voltage | $V_{(BR)}$ | V | $I_T$=1mA | 6.2 | | 7.3 |
| Forward voltage | $V_F$ | V | $I_F$=10mA | | | 0.9 |
| Clamping Voltage | $V_C$ (2) | V | $I_{PP}$=5A , $t_P$=8/20μs | | | 9.8 |
| Clamping Voltage | $V_C$ (2) | V | $I_{PP}$=15A , $t_P$=8/20μs | | | 15.5 |
| Junction Capacitance | $C_J$ | pF | $V_R$=0V,f=1MHz | | 140 | 400 |

(1).Other voltages available upon request.
(2).Non-repetitive current pulse 8/20μs exponential decay waveform according to IEC61000-4-5

## ■Ordering Information (Example)

| PREFERED P/N | PACKING CODE | UNIT WEIGHT(g) | MINIMUM PACKAGE(pcs) | INNER BOX QUANTITY(pcs) | OUTER CARTON QUANTITY(pcs) | DELIVERY MODE |
|---|---|---|---|---|---|---|
| ESD5V0D3 | F2 | Approximate 0.004 | 3000 | 30000 | 120000 | 7” reel |

## ■ Characteristics (Typical)

Fig. 1 - 8 X 20μs Pulse Waveform







Fig. 2 - Pulse Derating Curve




## ■ Outline Dimensions




| Symbol | Min. (mm) | Max. (mm) |
|---|---|---|
| A | | 1.000 |
| A1 | 0.000 | 0.100 |
| A2 | 0.800 | 0.900 |
| b | 0.250 | 0.400 |
| c | 0.080 | 0.150 |
| D | 1.200 | 1.400 |
| E | 1.600 | 1.800 |
| E1 | 2.500 | 2.700 |
| L | 0.475REF | |
| L1 | 0.250 | 0.400 |
| θ | 0° | 8° |

## ■ Soldering Footprint




Unit：inches

# Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.