
1-Line, Bi-directional, Transient Voltage Suppressor




Features


- Stand-off voltage: ±5V Max
- Transient protection for each line according to
  IEC61000-4-2(ESD): ±30kV (contact)
  IEC61000-4-4 (EFT): 40A (5/50ns)
  IEC61000-4-5(surge): 8A (8/20μs)
- Ultra-low capacitance: C_J = 10pF typ
- Low leakage current
- Low clamping voltage: V_{CL} =10V typ. @ I_{PP} = 16A (TLP)
- Solid-state silicon technology

Mechanical Data

- **Package**: SOD-523
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** No marking on bi-directional types
- **Marking:**



■Definitions of electrical characteristics



■Maximum Ratings

PARAMETER	SYMBOL	Rating	UNIT
Peak pulse power (t_p = 8/20μs)	P_{pk}	96	W
Peak pulse current (t_p = 8/20μs)	I_{PP}	8	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	±30	KV
ESD according to IEC61000-4-2 contact discharge		±30	KV
Junction temperature	T_J	125	℃
Operating temperature	T_{OP}	-40~85	℃
Storage temperature	T_{STG}	-55~150	℃

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V				±5.0
Reverse leakage current	I_R	nA	V_{RWM} =5V			100
Reverse breakdown voltage	V_{BR}	V	I_{BR} = 1mA	5.3	6	
Reverse holding voltage	V_{HOLD}	V	I_{HOLD} = 50mA	5.3	6	
Clamping voltage 1)	V_{CL}	V	I_{PP} = 16A, t_p = 100ns		10	
Dynamic resistance 1)	R_{DYN}	Ω			0.2	
Clamping voltage 2)	V_{CL}	V	V_{ESD} = 8kV		10	
Clamping voltage 3)	V_{CL}	V	I_{PP} = 1A, t_p = 8/20μs			8
		V	I_{PP} = 8A, t_p = 8/20μs			12
Junction capacitance	C_J	pF	V_R = 0V, f = 1MHz		10	13
		pF	V_R = 2.5V, f = 1MHz		8	11


(1). TLP parameter: Z_0 = 50Ω, t_p = 100ns, t_r = 2ns, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.
(2). Contact discharge mode, according to IEC61000-4-2.
(3). Non-repetitive current pulse, according to IEC61000-4-5.

■Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ESD5V0D5BS	F3	Approximate 0.9	3 000	30 000	120 000	Tape & reel

■ Characteristics (Typical)


8/20μs waveform per IEC61000-4-5




Contact discharge current waveform per IEC61000-4-2




Clamping voltage vs. Peak pulse current




Capacitance vs. Reverse voltage




Non-repetitive peak pulse power vs. Pulse time




Power derating vs. Ambient temperature




ESD clamping
(+8kV contact discharge per IEC61000-4-2)




ESD clamping
(-8kV contact discharge per IEC61000-4-2)



TLP Measurement




■ Outline Dimensions



Symbol	Min.(mm)	Max.(mm)
A	0.510	0.770
A1	0.500	0.700
b	0.250	0.350
c	0.080	0.150
D	0.750	0.850
E	1.100	1.300
E1	1.500	1.700
E2	0.200 Ref	
L	0.010	0.070
θ	7° Ref	

■ **Recommend land pattern** (Unit:mm)



Notes:
This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.