
ESD Protection Diode



Features

- For sensitive ESD protection
- Low leakage
- Uni-directional ESD protection of one line
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Mechanical Data

- **Package**: SOD523
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end
- **Marking:** ZH


■Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Operating Junction & Storage Temperature	T_J&T_{STG}	-45 to +125	℃
IEC61000-4-2(ESD)Air	VESD	±30	KV
IEC61000-4-2(ESD)Contact		±30	KV
Peak Pulse Current	I_{PP} (2)	8.8	A

(1).Non-repetitive current pulse 8/20μs exponential decay waveform according to IEC61000-4-5.

■Electrical Parameter

PARAMETER	SYMBOL
Clamping Voltage@ I_{PP}	V_C
Breakdown Voltage@ I_T	V_{BR}
Peak Pulse Current	I_{PP}
Test Current	I_T
Reverse Leakage Current@ V_{RWM}	I_R
Reverse Standoff Voltage	V_{RWM}
Forward Voltage@ I_F	V_F
Forward Current	I_F
Peak Power Dissipation	P_{Pk}
Max. Capacitance @ V_R=0 and f=1MHz	C



■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse Standoff Voltage	V_{RWM} (1)	V				7.0
Reverse Leakage Current	I_R	uA	VRWM=7.0V			0.03
Breakdown Voltage	$V_{(BR)}$	V	I_T=1mA	7.5		
Clamping Voltage	V_C (2)	V	I_{PP}=8.8A， tp=8/20us			22.7
Forward voltage	VF	V	IF=10mA			0.9
Peak Power Dissipation	Ppk	W	tp=8/20us			200
Junction Capacitance	C_J	pF	V_R=0V,f=1MHz		65	

(1).Other voltages available upon request.
(2).Non-repetitive current pulse 8/20 μs exponential decay waveform according to IEC61000-4-5

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ESD7V0D5	F2	Approximate 0.002	8000	80000	320000	7” reel

■ Characteristics (Typical)

Fig. 1 - 8 X 20μs Pulse Waveform







Fig. 2 - Pulse Derating Curve



■ Outline Dimensions



■ Soldering Footprint



Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.