
# 1-Line, Bi-directional, Transient Voltage Suppressor





## Features

- Stand-off voltage: ±5V Max
- Transient protection for each line according to
IEC61000-4-2(ESD): ±30kV (contact)
IEC61000-4-4 (EFT): 40A (5/50ns)
IEC61000-4-5(surge): 3.5A (8/20μs)
- Ultra-low capacitance: $C_J$ = 3pF typ
- Low leakage current
- Low clamping voltage: $V_{CL}$ =15.0V typ. @ $I_{PP}$ = 16A (TLP)
- Solid-state silicon technology

## Mechanical Data

- **Package**: DFN1006-2L
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** No marking on bi-directional types
- **Marking:** 5C

## ■Definitions of electrical characteristics



## ■Maximum Ratings

| PARAMETER | SYMBOL | Rating | UNIT |
|---|---|---|---|
| Peak pulse power ($t_p$ = 8/20μs) | $P_{pk}$ | 41 | W |
| Peak pulse current ($t_p$ = 8/20μs) | $I_{PP}$ | 3.5 | A |
| ESD according to IEC61000-4-2 air discharge | $V_{ESD}$ | ±30 | KV |
| ESD according to IEC61000-4-2 contact discharge | | ±30 | KV |
| Junction temperature | $T_J$ | 125 | ℃ |
| Operating temperature | $T_{OP}$ | -40~85 | ℃ |
| Storage temperature | $T_{STG}$ | -55~150 | ℃ |

.

## ■Electrical Characteristics（$T_a$=25℃ Unless otherwise specified）

| PARAMETER | Symbol | UNIT | Conditions | Min | Typ | Max |
|---|---|---|---|---|---|---|
| Reverse maximum working voltage | $V_{RWM}$ | V | | | | ±5 |
| Reverse leakage current | $I_R$ | nA | $V_{RWM}$ =5V | | | 100 |
| Reverse breakdown voltage | $V_{BR}$ | V | $I_{BR}$ = 1mA | 5.5 | | |
| Reverse holding voltage | $V_{HOLD}$ | V | $I_{HOLD}$ = 50mA | 5.5 | | |
| Clamping voltage 1) | $V_{CL}$ | V | $I_{PP}$ = 16A, $t_p$ = 100ns | | 15.0 | |
| Dynamic resistance 1) | $R_{DYN}$ | Ω | | | 0.35 | |
| Clamping voltage 2) | $V_{CL}$ | V | $V_{ESD}$ = 8kV | | 15.0 | |
| Clamping voltage 3) | $V_{CL}$ | V | $I_{PP}$ = 1A, $t_p$ = 8/20μs | | | 8.5 |
| | | V | $I_{PP}$ = 3.5A, $t_p$ = 8/20μs | | | 12 |
| Junction capacitance | $C_J$ | pF | $V_R$ = 0V, f = 1MHz | | 3 | 4 |
| | | pF | $V_R$ = 2.5V, f = 1MHz | | 2.4 | 3 |


(1). TLP parameter: $Z_0$ = 50Ω, $t_p$ = 100ns, $t_r$ = 2ns, averaging window from 60ns to 80ns. $R_{DYN}$ is calculated from 4A to 16A.
(2). Contact discharge mode, according to IEC61000-4-2.
(3). Non-repetitive current pulse, according to IEC61000-4-5.

## ■Ordering Information (Example)


| PREFERED P/N | UNIT WEIGHT(mg) | MINIMUM PACKAGE(pcs) | INNER BOX QUANTITY(pcs) | OUTER CARTON QUANTITY(pcs) | DELIVERY MODE |
|---|---|---|---|---|---|
| ESDLC5V0LB | Approximate 0.9 | 10000 | 100000 | 400000 | Tape& reel |

## ■ Characteristics (Typical)


**8/20μs waveform per IEC61000-4-5**





**Contact discharge current waveform per IEC61000-4-2**





**Clamping voltage vs. Peak pulse current**





**Capacitance vs. Reverse voltage**





**Non-repetitive peak pulse power vs. Pulse time**





**Power derating vs. Ambient temperature**




**ESD clamping**
**(+8kV contact discharge per IEC61000-4-2)**





**ESD clamping**
**(-8kV contact discharge per IEC61000-4-2)**





**TLP Measurement**




## ■ Outline Dimensions





Top View




Bottom View





Side View



| Symbol | Dimensions in Millimeters | | |
|---|---|---|---|
| | Min. | Typ. | Max. |
| A | 0.340 | 0.450 | 0.530 |
| A1 | 0.000 | 0.020 | 0.050 |
| A3 | | 0.125 Ref. | |
| D | 0.950 | 1.000 | 1.080 |
| E | 0.550 | 0.600 | 0.680 |
| b | 0.200 | 0.250 | 0.300 |
| L | 0.450 | 0.500 | 0.550 |
| e | | 0.650 BSC | |

## ■ Recommend land pattern (Unit:mm)




Notes:
This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met

# Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.