
4-Line, Uni-directional, Ultra-low Capacitance Transient Voltage Suppressor



Features

- Stand-off voltage: 3.3V Max
- Transient protection for each line according to
  IEC61000-4-2(ESD): ±30kV (contact)
  IEC61000-4-5(surge): 12A (8/20μs)
- Low leakage current
- Ultra-low capacitance: CJ = 0.4pF typ
- Low clamping voltage

V_{CL} = 8.8V typ. @ IPP = 16A (TLP)


- RoHS Compliant

Applications


- USB 2.0 and USB 3.0
- HDMI 1.3, HDMI 1.4 and HDMI 2.0
- SATA and eSATA interface
- DVI
- IEEE 1394
- Portable Electronics and Notebooks
- Ethernet port: 10/100/1000 Mbs/s
- Desktop and Notebooks PCS

Mechanical Data

- Package: DFN2510-10L
- Case Material: “Green” Molding Compound
- Marking Information: See Below



■Definitions of electrical characteristics



■Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power (t_p = 8/20μs)	P_{pk}	450	W
Peak pulse current (t_p = 8/20μs)	I_{PP}	12	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	±30	KV
ESD according to IEC61000-4-2 contact discharge		±30	
Junction temperature	T_J	125	℃
Storage temperature	T_{STG}	-55~150	℃

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V				3.3
Reverse leakage current	I_R	nA	V_{RWM} = 3.3V		<1	100
Reverse breakdown voltage	V_{BR}	V	I_T = 1mA	7	8	
Forward voltage	V_F	V	I_T = 20mA		0.83	
Clamping voltage [1)]	V_{CL}	V	I_{PP} = 16A, t_p = 100ns		8.8	
Dynamic resistance [1)]	R_{DYN}	Ω			0.18	
Clamping voltage [2)]	V_{CL}	V	V_{ESD} = +8kV		9	
Clamping voltage	V_{CL}	V	I_{PP} = 1A, t_p = 8/20μs		5	7
		V	I_{PP} =12A, t_p = 8/20μs		10	12
Junction capacitance	CJ	pF	V_R = 0V, f = 1MHz Any I/O pin to GND		0.40	0.65

Notes:

(1). TLP parameter: Z0 = 50Ω, tp = 100ns, tr = 2ns, averaging window from 60ns to 80ns. RDYN is calculated from 4A to 16A.

(2). Contact discharge mode, according to IEC61000-4-2.


(3). Non-repetitive current pulse, according to IEC61000-4-5

■Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ESDSLC3314P5	F1	Approximate 3.48	3000	30000	120000	7 reel

■ Characteristics (Typical)


8/20μs waveform per IEC61000-4-5




Contact discharge current waveform per IEC61000-4-2




Clamping voltage vs. Peak pulse current




Capacitance vs. Reverse voltage




Non-repetitive peak pulse power vs. Pulse time




Power derating vs. Ambient temperature



TLP Measurement




■ Outline Dimensions



Top View


Bottom View



Side View

Symbol	Dimensions in Millimeters		
	Min.	Typ.	Max.
A	0.500	0.575	0.650
A1	0.000	-	0.050
A3	0.150 Ref.		
D	2.400	2.500	2.600
E	0.900	1.000	1.100
D1	0.300	0.400	0.500
E1	0.300	0.455	0.610
b	0.130	0.190	0.250
e	0.500 BSC		
L	0.280	0.390	0.500

■ Soldering Footprint



Unit:mm

Notes:
This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.