
2-Lines, Uni-directional, Low Capacitance Transient Voltage Suppressor



Features

- Stand-off voltage: 3.3V Max
- Transient protection for each line according to
  IEC61000-4-2(ESD): ±30kV (contact)
  IEC61000-4-5(surge): 9A (8/20μs)
- Ultra-low capacitance: CJ = 1.2pF typ
- Ultra-low leakage current
- Low clamping voltage:

V_{CL} = 3.1V typ. @ IPP = 16A (TLP)

- RoHS Compliant


Applications

- USB 2.0
- HDMI 1.3, HDMI 1.4
- SATA and eSATA interface
- DVI
- IEEE 1394
- Portable Electronics and Notebooks


Caution:
This Device is designed for signal line protection only. Not intended to be used under bias, not for application with a power line.

Mechanical Data

- Package: DFN1006-3L
- Case Material: “Green” Molding Compound
- Moisture Sensitivity: Level 3 per J-STD-020
- Marking Information: See Below



■Definitions of electrical characteristics



■Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power (t_p = 8/20μs)	P_{pk}	45	W
Peak pulse current (t_p = 8/20μs)	I_{PP}	9	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	±30	kV
ESD according to IEC61000-4-2 contact discharge		±30	
Junction temperature	T_J	-55~125	ºC
Storage temperature	T_{STG}	-55~150	ºC

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V				3.3
Reverse leakage current	I_R	nA	V_{RWM} = 3.3V			50
Reverse breakdown voltage	V_{BR}	V	I_T =1mA	8.5		
Reverse holding voltage	V_{HOLD}	V	I_{HOLD} = 50mA,	1.8		
Clamping voltage 1)	V_{CL}	V	I_{PP} = 16A, t_p = 100ns		4.2	
Dynamic resistance 1)	R_{DYN}	Ω			0.1	
Clamping voltage 2)	V_{CL}	V	V_{ESD} = 8kV		5.5	
Clamping voltage 3)	V_{CL}	V	I_{PP} = 1A, t_p = 8/20μs		2.1	3.0
		V	I_{PP} = 9A, t_p = 8/20μs		3.2	5.0
Junction capacitance	C_J	pF	V_R = 1.5V, f = 1MHz		1.2	1.5

Notes:
(1). TLP parameter: Z_0 = 50Ω, t_p = 100ns, t_r = 2ns, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.
(2). Contact discharge mode, according to IEC61000-4-2.
(3). Non-repetitive current pulse, according to IEC61000-4-5.

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ESDSLC3V3LT	F1	Approximate 0.9	10000	100000	400000	7” reel

■ Characteristics (Typical)

Fig.1 8/20μs waveform per IEC61000-4-5




Fig.2 Contact discharge current waveform per IEC61000-4-2




Fig.3 Clamping voltage vs. Peak pulse current




Fig.4 Capacitance vs. Reverse voltage




Fig.5 Non-repetitive peak pulse power vs. Pulse time




Fig.6 Power derating vs. Ambient temperature




Fig.7 ESD clamping
(+8kV contact discharge per IEC61000-4-2)




Fig.8 ESD clamping
(-8kV contact discharge per IEC61000-4-2)






Fig.9 TLP Measurement



■ Outline Dimensions



SYMBOL	MILLIMETER	
	MIN	MAX
A	0.95	1.05
B	0.55	0.65
C	0.40	0.55
C1		0.05
D	0.01	0.08
E	0.675 BSC	
F	0.20	0.40
G	0.40	0.60
H	0.35 BSC	
I	0.10	0.20

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website http:// www.21yangjie.com , or consult your nearest Yangjie's sales office for further assistance.