
1-Line, Uni-directional, Transient Voltage Suppressor





DFN1006-2L

Features

- Ultra small package
- Stand-off voltage: 3.3V Max
- Transient protection for each line according to
  IEC61000-4-2(ESD): ±30kV (contact)
  IEC61000-4-5(surge): 8A (8/20μs)
- Ultra-low capacitance: CJ = 0.15 pF typ
- Low leakage current
- Low clamping voltage
- RoHS Compliant

Applications


- USB 2.0 , USB 3.0 , USB 3.1 and USB type-C
- HDMI 1.3, HDMI 1.4 and HDMI 2.0
- SATA and eSATA interface
- DVI
- IEEE 1394
- Portable Electronics and Notebooks
- Ethernet port: 10/100/1000 Mb/s
- Desktop and Notebooks PCs

Mechanical Characteristics

- Package: DFN1006-2L
- Case Material: “Green” Molding Compound.
- Marking Information: See Below



■Definitions of electrical characteristics



■Absolute Maximum Ratings (Ta=25°C unless otherwise specified)

PARAMETER	SYMBOL	Rating	UNIT
Peak pulse power (t_p = 8/20μs)	P_{pk}	112	W
Peak pulse current (t_p = 8/20μs)	I_{PP}	8	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	±30	KV
ESD according to IEC61000-4-2 contact discharge		±30	KV
Junction temperature	T_J	125	°C
Storage temperature	T_{STG}	-55~150	°C

■Electrical Characteristics (Ta=25℃ Unless otherwise specified)

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V				3.3
Reverse breakdown voltage	V_{BR}	V	I_{BR} = 1mA	5.5		
Forward voltage	V_F	V	I_T = 10mA		0.7	
Reverse leakage current	I_R	nA	V_{RWM} =3.3V			100
Clamping voltage 3)	V_{CL}	V	I_{PP} = 1A, t_p = 8/20μs			7.5
		V	I_{PP} = 8A, t_p = 8/20μs			14
Junction capacitance	C_J	pF	V_R = 0V, f = 1MHz Any I/O pin to GND		0.15	0.2


(1). TLP parameter: Z_0 = 50Ω, t_p = 100ns, t_r = 2ns, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.
(2). Contact discharge mode, according to IEC61000-4-2.
(3). Non-repetitive current pulse, according to IEC61000-4-5.

■Ordering Information (Example)


PREFERED P/N	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ESDULC3V3LB	Approximate 0.9	10000	100000	400000	Tae& reel

■ Typical Performance Characteristics (Ta=25℃ unless otherwise Specified)


8/20μs waveform per IEC61000-4-5




Contact discharge current waveform per IEC61000-4-2




Clamping voltage vs. Peak pulse current




Capacitance vs. Reverse voltage




Non-repetitive peak pulse power vs. Pulse time




Power derating vs. Ambient temperature




■ Outline Dimensions




Top View




Bottom View





Symbol	Dimensions in Millimeters		
	Min.	Typ.	Max.
A	0.340	-	0.550
A1	0.000	0.020	0.050
A3	0.125 Ref.		
D	0.950	1.000	1.075
E	0.550	0.600	0.675
b	0.200	0.250	0.300
L	0.450	0.500	0.550
e	0.650 BSC		

■ Recommend land pattern (Unit:mm)



Notes:
This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.