
2-Line, Uni-directional, Transient Voltage Suppressor



Features


- Stand-off voltage: 17V Max
- Transient protection for each line according to
  IEC61000-4-2(ESD): ±30kV (contact)
  IEC61000-4-5(surge): 12A (8/20μs)
- Low leakage current:
- Ultra low clamping voltage
- RoHS Compliant

Applications


- Cellular Handsets and Accessories
- Notebooks and Handhelds
- Portable Instrumentation
- Set Top Box
- Industrial Controls
- Server and Desktop PC

Mechanical Data

- Package: SOT-23
- Lead Finish: Matte Tin
- Case Material: “Green” Molding Compound
- Moisture Sensitivity: Level 1 per J-STD-020
- Marking Information: See Below



■Definitions of electrical characteristics



■Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power (t_p = 8/20μs)	P_{pk}	380	W
Peak pulse power (t_p = 10/1000μs)	P_{pk}	45	W
Peak pulse current (t_p = 8/20μs)	I_{PP}	12	A
Peak pulse current (t_p = 10/1000μs)	I_{PP}	1.6	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	±30	KV
ESD according to IEC61000-4-2 contact discharge		±30	
Junction temperature	T_J	125	°C
Storage temperature	T_{STG}	-55~150	°C

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V				17
Reverse leakage current	I_R	nA	V_{RWM} = 17V			50
Reverse breakdown voltage	V_{BR}	V	I_{BR} = 1mA	19	20	21
Clamping voltage [2]	V_{CL}	V	I_{PP} = 1A, t_p = 8/20μs		22	26
		V	I_{PP} = 12A, t_p = 8/20μs		27	32
Clamping voltage	V_{CL}	V	I_{PP} = 1.6A, t_p = 10/1000μs		24	28
Junction capacitance	C_J	pF	V_R = 0V, f = 1MHz Pin1/2-Pin3		77	90
		pF	V_R = 0V, f = 1MHz Pin1-Pin2		40	45

Notes:
(1). TLP parameter: Z_0 = 50Ω, t_p = 100ns, t_r = 2ns, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.
(2). Non-repetitive current pulse, according to IEC61000-4-5.

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MMBZ20VA	F2	Approximate 8	3000	30000	120000	7” reel

■ Characteristics (Typical)

Fig.1 8/20μs waveform per IEC61000-4-5




Fig.2 Contact discharge current waveform per IEC61000-4-2




Fig.3 Clamping voltage vs. Peak pulse current




Fig.4 Capacitance vs. Reverse voltage




Fig.5 Non-repetitive peak pulse power vs. Pulse time







Fig.6 Power derating vs. Ambient temperature




■ Outline Dimensions





Symbol	Dimensions in millimeters		
	Min.	Typ.	Max.
A	0.900	-	1.150
A1	0.000	-	0.100
A2	0.900	-	1.050
b	0.300	-	0.500
c	0.100	-	0.200
D	2.800	-	3.000
E	1.200	-	1.400
E1	2.250	-	2.550
e	0.950TYP		
e1	1.800	-	2.000
L	0.550REF		
L1	0.300	-	0.500
θ	0°	-	8°

■ Soldering Footprint



Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.