
4-Line, Uni-directional, Ultra-low Capacitance, Transient Voltage Suppressor



DFN2510

Features

- Stand-off voltage: 5V Max
- Transient protection for each line according to
  IEC61000-4-2(ESD): ±15kV (contact)
  IEC61000-4-5(surge): 7A (8/20μs)
- Ultra-low capacitance: C_J = 0.4 pF typ
- Low leakage current
- Low clamping voltage
- Up to 4 lines protects
- RoHS Compliant


Applications

- HDMI 2.0, USB 3.0/3.1 Type C
- Monitors and flat panel displays
- Set-top box and Digital TV
- MDDI ports
- Video graphics cards
- Digital Video Interface (DVI)
- Notebook Computers
- PCI Express and Serial SATA Ports

Caution:
This Device is designed for signal line protection only.
Do not operate under electrical bias or connect to a power line.


Mechanical Data

- Lead Finish: Matte Tin
- Case Material: "Green" Molding Compound.
- Moisture Sensitivity: Level 3 per J-STD-020
- Marking Information: See Below



0524L: Device Marking Code
Dot denotes Pin1

■Definitions of electrical characteristics



■Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power (t_p = 8/20μs)	P_{pk}	56	W
Peak pulse current (t_p = 8/20μs)	I_{PP}	7	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	±15	KV
ESD according to IEC61000-4-2 contact discharge		±15	
Junction temperature	T_J	-55~125	°C
Storage temperature	T_{STG}	-55~150	°C

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V	Any I/O pin to ground			5
Reverse leakage current	I_R	nA	V_{RWM} = 5V, any I/O pin to ground			200
Reverse breakdown voltage	$V_{(BR)}$	V	I_T = 1mA, any I/O pin to ground	6.0	8.0	10.0
Reverse holding voltage	V_{HOLD}	V	I_{HOLD} = 50mA, any I/O pin to ground		2	
Clamping voltage 1)	V_{CL}	V	I_{PP} = 16A, t_p = 100ns		3.2	
Clamping voltage 2)	V_{CL}	V	I_{PP} = 1A, t_p = 8/20μs		2.5	5
		V	I_{PP} = 7A, t_p = 8/20μs		4.5	8
Junction capacitance	CJ	pF	V_R = 0V, f = 1MHz Any I/O pin to GND		0.4	0.55
			V_R = 1.5V, f = 1MHz Any I/O pin to GND		0.3	0.45

Notes:

1) TLP parameter: Z_0 = 50Ω, t_p = 100ns, t_r = 2ns, averaging window from 60ns to 80ns.
2) Non-repetitive current pulse, according to IEC61000-4-5.

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SESDULC0504P5	F1	Approximate 3.48	3000	30000	120000	7 reel

■ Characteristics (Typical)

Fig.1 8/20μs waveform per IEC61000-4-5




Fig.2 Contact discharge current waveform per IEC61000-4-2




Fig.3 Clamping voltage vs. Peak pulse current




Fig.4 Capacitance vs. Reverse voltage




Fig.5 Non-repetitive peak pulse power vs. Pulse time




Fig.6 Power derating vs. Ambient temperature








Fig.7 TLP Measurement



■ Outline Dimensions








SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	0.40	0.45	0.50
A1	--	0.02	0.05
B	0.15	0.20	0.25
B1	0.35	0.40	0.45
C	0.10	0.15	0.20
D	2.45	2.50	2.55
E	0.95	1.00	1.05
F	0.50 BSC		
G	2.00 BSC		
H	0.30	0.38	0.46
R	0.125 BSC		
J	0.10	0.15	0.20

■ Soldering Footprint



SYM	DIMENSIONS	
	MILLIMETERS	INCHES
X1	0.200	0.008
X2	0.400	0.016
X3	0.600	0.024
Y	0.600	0.024
Z	1.400	0.056

Notes:
This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met.

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.