

ESD Protection Diode



Features

- ●Low clamping voltage
- ● Low leakage
- ●Operating voltage: 7V or 12V
- ● Marking:B712



■Maximum Ratings

PARAMETER	SYMBOL	VALUE	UNIT
Operating Junction	T_J	-55 to +125	℃
Storage Temperature	T_{STG}	-55 to +150	℃
IEC61000-4-2(ESD)Air	V_{ESD} (1)	±30	KV
IEC61000-4-2(ESD)Contact		±30	KV
Peak Pulse Power	P_{PP} (2)	325	W
Peak Pulse Current	I_{PP} (2)	13	A


(1).Device stressed with ten non-repetitive ESD pulses.
(2).Non-repetitive current pulse 8/20μs exponential decay waveform according to IEC61000-4-5.

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）


PARAMETER	SYMBOL	UNIT	CONDITIONS		MIN	TYP	MAX
Reverse Standoff Voltage	V_{RWM} (1)	V	Pin 1 to Pin 3 and Pin2 to Pin 3				12
			Pin 3 to Pin 1 and Pin3 to Pin 2				7
Reverse Leakage Current	I_R	uA	Pin 1 to Pin 3 and Pin2 to Pin 3	VR = V_{RWM}			0.5
			Pin 3 to Pin 1 and Pin3 to Pin 2	VR = V_{RWM}			0.5
Breakdown Voltage	$V_{(BR)}$	V	Pin 1 to Pin 3 and Pin2 to Pin 3	IT = 1mA	13.3		
			Pin 3 to Pin 1 and Pin3 to Pin 2	IT = 1mA	7.7		
Clamping Voltage	V_C (2)	V	Pin 1 to Pin 3 and Pin2 to Pin 3	I_{PP} = 5A			20
			Pin 3 to Pin 1 and Pin3 to Pin 2	I_{PP} = 5A			14
Clamping Voltage	V_C (2)	V	Pin 1 to Pin 3 and Pin2 to Pin 3	I_{PP} =13A			25
			Pin 3 to Pin 1 and Pin3 to Pin 2	I_{PP} = 13A			16
Junction Capacitance	C_J	pF	Pin 1 to Pin 3 and Pin2 to Pin 3	VR = 0V, f = 1MHz			40
			Pin 3 to Pin 1 and Pin3 to Pin 2	VR = 0V, f = 1MHz			40
Junction Capacitance	C_J	pF	Pin 1 to Pin 3 and Pin2 to Pin 3	VR = V_{RWM}, f = 1MHz			20
			Pin 3 to Pin 1 and Pin3 to Pin 2	VR = V_{RWM}, f = 1MHz			30

(1).Other voltages available upon request.
(2).Non-repetitive current pulse 8/20μs exponential decay waveform according to IEC61000-4-5


■ Characteristics (Typical)




Junction Capacitance vs. Reverse Voltage




Peak Pulse Power vs. Pulse Time




Clamping Voltage vs. Peak Pulse Current



Power Derating Curve




8 X 20μs Pulse Waveform



ESD Clamping Voltage


8 kV Contact per IEC61000−4−2

■ Outline Dimensions



SYM	DIMENSIONS					
	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.90	--	1.15	0.035	--	0.045
A1	0.00	--	0.10	0.000	--	0.004
A2	0.90	--	1.05	0.035	--	0.041
b	0.30	--	0.50	0.012	--	0.020
c	0.08	--	0.15	0.003	--	0.006
D	2.80	--	3.00	0.110	--	0.118
E	1.20	--	1.40	0.047	--	0.055
E1	2.25	--	2.55	0.089	--	0.100
e	0.95TYP			0.037TYP		
e1	1.80	--	2.00	0.071	--	0.079
L	0.55REF			0.022REF		
L1	0.30	--	0.50	0.012	--	0.020
θ	0°	--	8°	0°	--	8°

■ Soldering Footprint



SYM	DIMENSIONS	
	INCHES	MILLIMETERS
C	(.087)	(2.20)
E	.037	0.95
E1	.075	1.90
G	.031	0.80
X	.039	1.00
Y	.055	1.40
Z	.141	3.60

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.