
1- Line, Uni-directional, Transient Voltage Suppressor



Features


- Stand-off voltage: 3.3V Max
- Transient protection for each line according to
  IEC61000-4-2(ESD): ±30kV (contact)
  IEC61000-4-5(surge): 22A (8/20μs)
- Low leakage current
- Ultra-low capacitance: CJ = 3 pF typ
- Low clamping voltage
- RoHS Compliant

Applications


- Video Line Protection
- Wireless Systems
- Ethernet 10BaseT
- I2C Bus Protection
- Portable Instrumentation
- LAN/WAN equipment
- High-Speed Data Lines
- Multi-Protocol Serial Transceivers
- ISDN S/T Interface

Mechanical Data

- Package: SOT-143
- Case Material: “Green” Molding Compound
- Marking Information: See Below



■Definitions of electrical characteristics



■Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power (t_p = 8/20μs)，VCC pin to ground	P_{pk}	420	W
Peak pulse power (t_p = 8/20μs)，any I/O pin to ground	P_{pk}	264	W
Peak pulse current (t_p = 8/20μs)，VCC pin to ground	I_{PP}	35	A
Peak pulse current (t_p = 8/20μs)，any I/O pin to ground	I_{PP}	22	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	±30	KV
ESD according to IEC61000-4-2 contact discharge		±30	
Junction temperature	T_J	-55~125	℃
Storage temperature	T_{STG}	-55~150	℃

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V	Any I/O Pin to ground			3.3
Reverse breakdown voltage	$V_{(BR)}$	V	I_T = 1mA,	4		
Reverse leakage current	I_R	uA	V_{RWM} = 3.3V,			0.5
Clamping voltage	V_{CL}	V	I_{PP} = 35A, t_p = 8/20μs，VCC pin to ground		.	12
		V	I_{PP} = 1A, t_p = 8/20μs，any I/O pin to ground		.	7
		V	I_{PP} = 22A, t_p = 8/20μs any I/O pin to ground			12
Junction capacitance	CJ	pF	VR = 0V, f = 1MHz, VCC pin to ground		90	
		pF	VR = 0V, f = 1MHz,any I/O pin to ground		3	.

Notes:

(1). TLP parameter: Z0 = 50Ω, tp = 100ns, tr = 2ns, averaging window from 60ns to 80ns. RDYN is calculated from 4A to 16A.

(2). Contact discharge mode, according to IEC61000-4-2.


(3). Non-repetitive current pulse, according to IEC61000-4-5

■Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SR33	F1	Approximate 12	3000	30000	120000	7 reel

■ Characteristics (Typical)


8/20μs waveform per IEC61000-4-5




Contact discharge current waveform per IEC61000-4-2




Clamping voltage vs. Peak pulse current




Capacitance vs. Reverse voltage



Non-repetitive peak pulse power vs. Pulse time





Power derating vs. Ambient temperature




ESD clamping
(8kV contact discharge per IEC61000-4-2)

TLP Measurement






■ Outline Dimensions



DIMENSIONS						
DIM	INCHES			MILLIMETERS		
	MIN	NOM	MAX	MIN	NOM	MAX
A	.031	-	.048	0.80	-	1.22
A1	.000	-	.006	0.013	-	0.15
A2	.029	.035	.042	0.75	0.90	1.07
b	.011	-	.020	0.30	-	0.51
b1	.029	-	.037	0.76	-	0.94
c	.003	-	.008	0.08	-	0.20
D	.110	.114	.120	2.80	2.90	3.04
E	.082	.093	.104	2.10	2.37	2.64
E1	.047	.051	.055	1.20	1.30	1.40
e	.075			1.92 BSC		
e1	.008			0.20 BSC		
L	.015	.020	.024	0.40	0.50	0.60
L1	(.021)			(0.54)		
N	4			4		
θ	0°	-	8°	0°	-	8°
aaa	.006			0.15		
bbb	.008			0.20		
ccc	.004			0.10		

■ Soldering Footprint



SYM	DIMENSIONS	
	MILLIMETERS	INCHES
C	2.20	0.087
E1	1.92	0.076
E2	1.72	0.068
G	0.80	0.031
X1	1.00	0.039
X2	1.20	0.047
Y	1.40	0.055
Z	3.60	0.141

Notes:
This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.