


Schottky Rectifier Modules

VRRM 200V
IFAV 300 A

Circuit



Applications

- Inversion Welder
- Plating Power Supply
- Gemeral Power Supply
- Ultrasonic Cleaner and Welder
- Converter & Chopper

Features

- Low Reverse Recovery Loss
- Low Forward Voltage
- High Surge Current Capability
- Popular SOT-227 Package

Maximum Ratings

Symbol	Conditions	Values	Units
V_R		200	V
I_{FAV}	T_C=105°C, Per Module	300	A
I_{FSM}	t=10ms T_J=25℃	4000	A
I^2t	t=10ms T_J=25℃	80000	A^2s
V_{ISO}	AC 50Hz/60Hz; R.M.S; 1min	3000	V
T_J		-40 to +150	℃
Tstg		-40 to +125	℃
V_{ISO}	AC 50Hz/60Hz; R.M.S; 1min	3000	V
Mt	To Terminals(M4)	1±15%	N·m
Ms	To Heatsink(M4)	1±15%	N·m
Weight		27	g

Thermal Characteristics

Symbol	Conditions	Values	Units
Rth(j-c)	Junction to Case(Per Leg)	0.15	℃/W

Electrical Characteristics

Symbol	Conditions	Values			Units
		Min.	Typ.	Max.	
I_{RM}	V_R=V_{RRM}	--	--	1	mA
	V_R=V_{RRM}, T_J=125°C	--	--	20	mA
VF	I_F=300A	--	--	1.1	V
	I_F=300A, T_J=125°C	--	--	1.0	V
r_F	T_J=125℃		0.7		mΩ
VF0			0.7		V

Performance Curves




Fig1. Power dissipation




Fig2.Forward Current Derating Curve




Fig3. Transient thermal impedance




Fig4. Max Non-Repetitive Forward Surge Current





Fig5. Forward Characteristics

Package Outline Information

CASE: FJ



DIM	Min (mm)	Max (mm)	Note
A	37.5	38.5	
B	27.5	28.5	
C	12.8	13.5	
D	29.5	30.5	
E	12.1	13.1	
F	14.5	15.5	
G	4.0	4.4	Ø
H	3.7	4.3	
I	3.3	3.9	
J	9.5	10.5	
K	3.7	4.3	
L	5.0	5.5	
M	4.0	4.4	
N	11.7	12.3	
O	1.8	2.2	

Packing Standard

Item	Length: A(mm)	Width: B(mm)	Height: C (mm)	Quantity (PCS)
Inner Box	290	252	40	25
Outer Carton	300	270	280	150

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.