

Glass Passivated Three Phase Rectifier Bridge

V_{RRM} 1800-2000V
I_D 100 A


Applications

- Three phase rectifiers for power supplies
- Rectifiers for DC motor field supplies
- Battery charger rectifiers
- Input rectifiers for variable frequency drives

Features

- Three phase bridge rectifier
- Blocking voltage:1800-2000V
- Heat transfer through aluminum oxide DBC ceramic isolated metal baseplate
- Glass passivated chip

Circuit



Module Type

TYPE	V_{RRM}	V_{RSM}
MD100S18M2 MD100S20M2	1800V 2000V	1900V 2100V

Maximum Ratings

Symbol	Conditions	Values	Units
I_D	Three phase, full wave Tc=100℃	100	A
I_{FSM}	t=10mS Tvj =45℃	750	A
i^2t	t=10mS Tvj =45℃	2800	A^2s
V_{isol}	a.c.50HZ;r.m.s.;1min	3000	V
T_{vj}		-40 to +150	℃
T_{stg}		-40 to +125	℃
Mt	To terminals(M5)	3±15%	Nm
Ms	To heatsink(M5)	3±15%	Nm
Weight	Module (Approximately)	130	g

Thermal Characteristics

Symbol	Conditions	Values	Units
Rth(j-c)	Per diode	1.0	℃/W
Rth(c-s)	Module (Approximately)	0.07	℃/W

Electrical Characteristics

Symbol	Conditions	Values			Units
		Min.	Typ.	Max.	
V_{FM}	T=25℃ I_F =150A	—	1.38	1.60	V
I_{RD}	T_{vj}=25℃ V_{RD}=V_{RRM} T_{vj}=150℃ V_{RD}=V_{RRM}	—	—		mA mA

Performance Curves




Fig1. Forward Characteristics




Fig2. Power dissipation




Fig3. Transient thermal impedance




Fig4. Max Non-Repetitive Forward Surge Current





Fig5.Forward Current Derating Curve

Package Outline Information

CASE:M2



DIM	Min (mm)	Max (mm)	Note
A	71.5	72.5	
B	41.5	42.5	
C	39.5	40.5	
D	22.7	23.3	
E	59.5	60.5	
F	47.5	48.5	
G	53.5	54.5	
H	29.5	30.5	
I	2.9	3.1	
J	21.3	21.9	
K	5.4	5.6	Ø
L	10	11	
M	5.2	5.8	

Packing Standard

Item	Length: A (mm)	Width: B (mm)	Height: C (mm)	Quantity (PCS)
Inner Box	276	258	48	8
Outer Carton	545	295	240	80

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.