


Glass Passivated Single Phase Rectifier Bridge

V_{RRM} 800 to 2000V
ID 50 A



Applications

- Non-controllable rectifiers for AC/AC converters
- Line rectifiers for transistorized AC motor controllers
- Field supply for DC motors

Features

- Blocking voltage:800 to 2000V
- Heat transfer through aluminum oxide DBC ceramic isolated metal baseplate
- Glass passivated chip

Module Type

TYPE	V_{RRM}	V_{RSM}
MD50HV08FJ	800V	900V
MD50HV12FJ	1200V	1300V
MD50HV16FJ	1600V	1700V
MD50HV18FJ	1800V	1900V
MD50HV20FJ	2000V	2100V

Maximum Ratings

Symbol	Conditions	Values	Units
I_D	Single phase,Sin Full Wave Tc=105℃	50	A
I_{FSM}	t=10ms T_J=25℃	650	A
I^2t	t=10ms T_J=25℃	2100	A^2s
V_{ISO}	AC 50Hz/60Hz; R.M.S; 1min	3000	V
T_J		-40 to +150	℃
Tstg		-40 to +125	℃
Mt	To Terminals(M4)	2±15%	N·m
Ms	To Heatsink(M4)	2±15%	N·m
Weight		30	g

Thermal Characteristics

Symbol	Conditions	Values	Units
Rth(j-c)	Junction to Case(Per Diode)	0.6	℃/W
Rth(c-s)	Case to Heat Sink	0.3	℃/W

Electrical Characteristics

Symbol	Conditions	Values			Units
		Min.	Typ.	Max.	
V_{FM}	T_J=25℃ I_F =100A	—	1.2	1.4	V
I_{RD}	T_J=150℃ V_R=V_{RRM}	—	—	5	mA
r_F	T_J=125℃		4.5		mΩ
VF0			0.8		V

Performance Curves




Fig1. Power dissipation




Fig2.Forward Current Derating Curve




Fig3. Transient thermal impedance




Fig4. Max Non-Repetitive Forward Surge Current





Fig5. Forward Characteristics

Package Outline Information

CASE: FJ



DIM	Min (mm)	Max (mm)	Note
A	37.5	38.5	
B	27.5	28.5	
C	12.8	13.5	
D	29.5	30.5	
E	12.1	13.1	
F	14.5	15.5	
G	4.0	4.4	Ø
H	3.7	4.3	
I	3.3	3.9	
J	9.5	10.5	
K	3.7	4.3	
L	5.0	5.5	
M	4.0	4.4	
N	11.7	12.3	
O	1.8	2.2	

Packing Standard

Item	Length: A(mm)	Width: B(mm)	Height: C (mm)	Quantity (PCS)
Inner Box	290	252	40	25
Outer Carton	300	270	280	150

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.