STARSEA


MF200DU06FJ

RoHS COMPLIANT



FRED Modules

VRRM 600V
IFAV 2*100 A



Applications

- Inversion Welder
- Plating Power Supply
- Ultrasonic Cleaner and Welder
- Power Factor Correction (PFC) Circuit
- Converter & Chopper

Features

- Soft Reverse Recovery Characteristics
- Ultrafast Reverse Recovery Time
- Low Reverse Recovery Loss
- Low Forward Voltage
- High Surge Current Capability
- Popular SOT-227 Package

Maximum Ratings

Symbol	Conditions	Values	Units
V_R		600	V
I_{FAV}	T_C=100°C, Per Diode	100	A
	T_C=100°C, Per Module	200	A
I_{FRMS}	T_C=100°C, Per Diode	140	A
I_{FSM}	t=10ms T_J=25℃	1500	A
I^2t	t=10ms T_J=25℃	11250	A^2s
P_D		357	W
V_{ISO}	AC 50Hz/60Hz; R.M.S; 1min	3000	V
T_J		-40 to +150	°C
Tstg		-40 to +125	°C
Mt	To Terminals(M4)	1±15%	N·m
Ms	To Heatsink(M4)	1±15%	N·m
Weight		27	g

Thermal Characteristics

Symbol	Conditions	Values	Units
Rth(j-c)	Junction to Case(Per Leg)	0.35	℃/W
Rth(c-h)	Case to Heat Sink	0.2	℃/W

Electrical Characteristics

Symbol	Conditions	Values			Units
		Min.	Typ.	Max.	
I_{RM}	V_R=600V	--	--	0.5	mA
	V_R=600V, T_J=125°C	--	--	5	mA
V_F	I_F=100A	--	1.20	1.40	V
	I_F=100A, T_J=125°C	--	1.05	1.25	V
trr	I_F=1A, V_R=30V, d_{iF}/dt=-200A/μs	--	42	--	ns
trr	V_R=300V, I_F=100A, d_{iF}/dt=-200A/μs, T_J=25°C	--	105	--	ns
I_{RRM}		--	10	--	A
trr	V_R=300V, I_F=100A, d_{iF}/dt=-200A/μs, T_J=125°C	--	200	--	ns
I_{RRM}		--	18	--	A

Performance Curves




Fig1. Forward Voltage Drop vs Forward Current




Fig2. Reverse Recovery Time vs diF/dt




Fig3. Transient thermal impedance





Fig4. Max Non-Repetitive Forward Surge Curr

Package Outline Information

CASE: FJ



DIM	Min (mm)	Max (mm)	Note
A	37.5	38.5	
B	27.5	28.5	
C	12.8	13.5	
D	29.5	30.5	
E	12.1	13.1	
F	14.5	15.5	
G	4.0	4.4	Ø
H	3.7	4.3	
I	3.3	3.9	
J	9.5	10.5	
K	3.7	4.3	
L	5.0	5.5	
M	4.0	4.4	
N	11.7	12.3	
O	1.8	2.2	

Packing Standard

Item	Length: A (mm)	Width: B (mm)	Height: C (mm)	Quantity (PCS)
Inner Box	290	252	40	25
Outer Carton	300	270	280	150

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.