


# FRED Modules

**VRRM** 400V
**IFAV** 400 A




## Applications

- Inversion Welder
- Plating Power Supply
- Ultrasonic Cleaner and Welder
- Power Factor Correction (PFC) Circuit
- Converter & Chopper

## Features

- Soft Reverse Recovery Characteristics
- Ultrafast Reverse Recovery Time
- Low Reverse Recovery Loss
- Low Forward Voltage
- High Surge Current Capability

## Maximum Ratings

| Symbol | Conditions | Values | Units |
|---|---|---|---|
| $V_R$ | | 400 | V |
| $V_{RRM}$ | | 400 | V |
| $I_{FAV}$ | $T_C$=100°C, Per Leg | 200 | A |
| | $T_C$=100°C, Per Module | 400 | A |
| $I_{FRMS}$ | $T_C$=100°C, Per Leg | 280 | A |
| $I_{FSM}$ | t=10ms $T_J$=25℃ | 3200 | A |
| $I^2t$ | t=10ms $T_J$=25℃ | 51200 | $A^2s$ |
| $P_D$ | | 1040 | W |
| $T_J$ | | -40 to +150 | ℃ |
| Tstg | | -40 to +125 | ℃ |
| Mt | To Terminals(M6) | 5±15% | N·m |
| Ms | To Heatsink(M6) | 5±15% | N·m |
| Weight | | 85 | g |

## Thermal Characteristics

| Symbol | Conditions | Values | Units |
|---|---|---|---|
| Rth(j-c) | Junction to Case(Per Leg) | 0.12 | ℃/W |

## Electrical Characteristics

| Symbol | Conditions | Values | | | Units |
|---|---|---|---|---|---|
| | | Min. | Typ. | Max. | |
| $I_{RM}$ | $V_R$=400V | -- | -- | 0.5 | mA |
| | $V_R$=400V, $T_J$=125°C | -- | -- | 5 | mA |
| $V_F$ | $I_F$=200A | -- | 1.0 | 1.2 | V |
| | $I_F$=200A, $T_J$=125°C | -- | 0.9 | 1.1 | V |
| trr | $I_F$=1A, $V_R$=30V, $di_F/dt$=-200A/μs | -- | 80 | -- | ns |
| trr | $V_R$=200V, $I_F$=200A, $di_F/dt$=-200A/μs, TJ=25°C | -- | 140 | -- | ns |
| $I_{RRM}$ | | -- | 16 | -- | A |
| trr | $V_R$=200V, $I_F$=200A, $di_F/dt$=-200A/μs, TJ=125°C | -- | 240 | -- | ns |
| $I_{RRM}$ | | -- | 30 | -- | A |

## Performance Curves





Fig1. Forward Characteristics





Fig2.Reverse Recovery Time vs $di_F/dt$





Fig3. Reverse Recovery Current vs $di_F/dt$






Fig4. Reverse Recovery Charge vs diF/dt

## Package Outline Information

### CASE: F3




| DIM | Min (mm) | Max (mm) | Note |
|---|---|---|---|
| A | 91.5 | 92.5 | |
| B | 26.5 | 27.5 | |
| C | 34.5 | 35.5 | |
| D | 79.5 | 80.5 | |
| E | 59.5 | 60.5 | |
| F | 16.5 | 17.5 | |
| G | 2.8 | 3.2 | |
| H | 6.2 | 6.8 | Ø |
| I | 13.8 | 14.2 | |
| J | 16.5 | 17.5 | |
| K | 8.5 | 9.5 | |
| L | 18.2 | 18.8 | |

## Packing Standard

| Item | Length: A(mm) | Width: B(mm) | Height: C (mm) | Quantity (PCS) |
|---|---|---|---|---|
| Inner Box | 276 | 258 | 40 | 10 |
| Outer Carton | 545 | 295 | 240 | 120 |

## Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.