

Thyristor Modules

V_{RRM} / V_{DRM}	800 to 1800V
I_{TAV}	110 A


Applications

- Power Converters
- Lighting Control
- DC Motor Control and Drives
- Heat and temperature control

Features

- International standard package
- High Surge Capability
- Glass passivated chip
- Simple Mounting
- Heat transfer through aluminum oxide DBC ceramic isolated metal baseplate

Circuit



Module Type

TYPE	V_{RRM}/V_{DRM}	V_{RSM}
MT110C08T1	800V	900V
MT110C12T1	1200V	1300V
MT110C16T1	1600V	1700V
MT110C18T1	1800V	1900V

Maximum Ratings

Symbol	Conditions	Values	Units
I_{TAV}	Single phase ,half wave 180°conduction Tc=85□	110	A
I_{TSM}	t=10ms T_J =25□	2400	A
I^2t	t=10ms T_J =25□	28800	A^2s
V_{ISO}	AC 50Hz/60Hz; R.M.S; 1min	3000	V
T_J		-40 to +125	□
Tstg		-40 to +125	□
Mt	To Terminals(M5)	3±15%	N·m
Ms	To Heatsink(M6)	5±15%	N·m
di/dt	T_j =125□, 2/3V_{DRM} ,I_G =500mA Tr<0.5us,tp>6us	150	A/us
a	Maximum allowable acceleration	50	m/s^2
Weight		90	g

Thermal Characteristics

Symbol	Conditions	Values	Units
Rth(j-c)	Junction to Case(Per Thyristor)	0.28	□/W
Rth(c-s)	Case to Heat Sink	0.1	□/W

Electrical Characteristics

Symbol	Conditions	Values			Units
		Min.	Typ.	Max.	
V_{TM}	T_J =25□ IT=300A			1.6	V
I_{RRM}/I_{DRM}	T_J =125□ ,V_R=V_{RRM} ,V_D=V_{DRM}			20	mA
V_{T0}	T_J =125□			0.85	V
rT	T_J =125□			2.5	mΩ
V_{GT}	T_J =25□, V_D =6V			3	V
I_{GT}	T_J =25□, V_D =6V			150	mA
V_{GD}	T_J =125□, V_D =2/3V_{DRM}			0.25	V
I_{GD}	T_J =125□, V_D =2/3V_{DRM}			6	mA
I_L	T_J =25□, R_G = 33 Ω		100	300	mA
I_H	T_J =25□, V_D =6V		70	200	mA
t_{gd}	T_J =25□, I_G=1A, diG/dt=1A/us		1		us
t_q	T_J =125□		100		us
dv/dt	T_J =125□,2/3V_{DRM}, Linear voltage rise		1000		V/us

Performance Curves




Fig1. Power dissipation




Fig2.Forward Current Derating Curve




Fig3. Transient thermal impedance




Fig4. Max Non-Repetitive Forward Surge Curre





Fig5. Gate trigger Characteristics

Package Outline Information

CASE: T1



DIM	Min (mm)	Max (mm)	Note
A	92.5	93.5	
B	79.5	80.5	
C	20.5	21.5	
D	13.5	14.5	
E	5.5	6.5	
F	10.5	11.5	
G	6.2	6.8	Ø
H	29.5	30.5	
I	28.5	29.5	
J	19.5	20.5	
K	2.3	3.5	
L	8.2	8.8	
M	8.5	9.5	

Packing Standard

Item	Length: A(mm)	Width: B(mm)	Height: C (mm)	Quantity (PCS)
Inner Box	276	258	48	10
Outer Carton	545	295	240	120

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.