

Small-Signal Fast Switching Diodes





Features

- VR 75V
- I_{FAV} 200mA

Typical Applications

- Extreme fast switches

Mechanical Data

- **Package**: SOD523
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end
- **Marking: E6**

■Maximum Ratings (T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	Conditions	VALUE
Reverse voltage	V_R	V	IR=100uA	75
Peak forward surge current	I_{FSM}	A	Pulse width=1 us Pulse width=1 s	2 0.5
Average forward current	I_{FAV}	mA		200
Power dissipation	P_D	mW		150
Maximum junction temperature	T_j	℃		-55 to +150
Storage temperature range	T_{stg}	℃		-55 to +150


■Electrical Characteristics（T_a=25℃ Unless otherwise specified）


PARAMETER	Symbol	UNIT	Conditions	Min	Max
Breakdown Voltage	V_R	V	IR=100uA	75	
Forward Voltage	V_F	V	IF=1mA		0.715
			IF=10mA		0.855
			IF=50mA		1.00
			IF=150mA		1.25
Reverse Leakage Current	I_R	uA	VR=75V		1
Capacitance	C	pF	VR=0V,f=1MHz		4
Reverse Recovery Time	Trr	ns	IF=IR=10mA，Irr=0.1*IR, RL=100Ω		6


■Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
BAS16X	F2	Approximate 0.002	8000	80000	320000	7” reel

■ Characteristics (Typical)











■ Outline Dimensions



DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MN	MAX
A	0.059	0.067	1.500	1.700
B	0.043	0.051	1.100	1.300
C	0.028	0.035	0.700	0.900
D	0.010	0.014	0.250	0.350
E	0.002	0.008	0.050	0.200
F	0.020	0.028	0.500	0.700

■ Soldering Footprint



Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.