
Small-Signal Fast Switching Diodes



Features

- VR 100V
- I_{FAV} single diode loaded 215mA
  double diode loaded 125mA

Typical Applications

- Low-Leakage

Mechanical Data

- **Package**: SOT23
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** JX

■Maximum Ratings (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Conditions	VALUE
Repetitive peak reverse voltage	V_{RRM}	V		100
Reverse voltage	V_R	V	IR=100uA	100
Peak forward surge current	IFSM	A	Non-Repetitive t = 1 μs	4
Average forward current	I_{FAV}	mA	single diode loaded	215
			double diode loaded	125
Power dissipation	P_{tot}	mW		250
Maximum junction temperature	T_j	℃		150
Storage temperature range	T_{stg}	℃		-55 to +150


■Electrical Characteristics (Ta=25℃ Unless otherwise specified)


PARAMETER	Symbol	UNIT	Conditions	Min	Max
Breakdown Voltage	V_R	V	IR=100uA	100	
Forward Voltage	V_F	V	IF=1mA		0.9
			IF=10mA		1.0
			IF=50mA		1.1
			IF=150mA		1.25
Reverse Leakage Current	I_R	nA	VR=75V		5
Capacitance	C	pF	VR=0V,f=1MHz		4
Reverse Recovery Time	Trr	us	IF=IR=10mA，Irr=0.1*IR, RL=100Ω		3


■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
BAV170	F2	Approximate 0.008	3000	30000	120000	7” reel


■ Characteristics (Typical)








■SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

■SOT-23Suggested Pad Layout



Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.