
NPN General Purpose Amplifier



Features

- Epoxy meets UL-94 V-0 flammability rating
- Halogen free available upon request by adding suffix ”HF”
- Moitsure Sensitivity Level 1
- Low collector-emitter saturation voltage

Mechanical Data

- **Package**: SOT-89

Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free

- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- Marking: BL

■Maximum Ratings (Ta=25℃ unless otherwise noted)

Item	Symbol	Unit	Conditions	Value
Minimum Collector-Emitter Voltage	V_{CEO}	V	I_C=10mA, I_B=0	80
Minimum Collector-Base Voltage	V_{CBO}	V	I_C=100uA, I_E=0	100
Minimum Emitter-Base Voltage	V_{EBO}	V	I_E=10uA, I_C=0	5
Collector Current	I_C	A		1
Collector Power Dissipation	P_C	mW		500
Thermal Resistance From Junction To Ambient	$R_{\theta JA}$	℃/W		250
Operation Junction Temperature	T_j	℃		-55 to +150
Storage Temperature	T_{stg}	℃		-55 to +150


■Electrical Characteristics (Ta=25℃ unless otherwise noted)


Item	Symbol	Unit	Conditions	Min	TYP	Max
Collector-Emitter Voltage	V_{CEO}	V	I_C=10mA, I_B=0	80		
Collector-Base Voltage	V_{CBO}	V	I_C=100uA, I_E=0	100		
Emitter-Base Voltage	V_{EBO}	V	I_E=10uA, I_C=0	5		
Collector-Base cut-off current	I_{CBO}	nA	V_{CB}=30V			100
Emitter-Base cut-off current	I_{EB0}	nA	V_{EB}=5V			100
DC Current Gain	$h_{FE(1)}$		V_{CE}=2V I_C=150mA	63		250
	$h_{FE(2)}$		V_{CE}=2V I_C=5mA	40		
	$h_{FE(3)}$		V_{CE}=2V I_C=500mA	25		
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	V	I_C=500mA I_B=50mA			0.5
Base-Emitter Voltage	V_{BE}	V	V_{CE}=2V I_C=500mA			1
Transition Frequency	f_T	MHz	I_C=10mA, V_{CE}=5V,f=100MHz		130	

■Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
BCX56	F2	Approximate 0.055	1000	8000	32000	7” reel

■Characteristics (Typical)







Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage




Base-Emitter On Voltage




Cob/Cib-V_{CB}/V_{EB}



Collector Power Derating Curve




■SOT-89 Package Outline Dimensions



BOTTOM VIEW


SIDE VIEW



SIDE VIEW

DIMENSIONS				
DIM	INCHES		MM	
	MIN.	MAX.	MIN.	MAX.
A	0.173	0.181	4.400	4.600
B	0.061 TYP.		1.550 TYP.	
C	0.155	0.167	3.940	4.250
D	0.031	0.047	0.800	1.200
E	0.094	0.102	2.400	2.600
F	0.118 TYP.		3.00 TYP.	
G	0.014	0.019	0.360	0.480
H	0.017	0.022	0.440	0.560
J	0.014	0.017	0.350	0.440
K	0.055	0.063	1.400	1.600
L	0.059 TYP.		1.500 TYP.	
M	0.108 TYP.		2.750 TYP.	

■SOT-89 Suggested Pad Layout



UNIT:MM

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.