

Dual Switching Diode





SOT-23

Features

- Moisture sensitivity level 1
- Reverse voltage: 80V
- Average forward current : 100mA

Application

- Signal switching
- High frequency rectifier

Mechanical data

- **Package**: SOT-23
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ **Maximum Ratings** (T_a=25℃ Unless otherwise specified)

Parameter	Symbol	Unit	Value
Device marking code			P
Repetitive peak reverse voltage	V_{RRM}	V	80
Forward current, per leg	I_F	mA	100
Non-repetitive Surge peak forward current @ t=8.3ms half-sine wave	I_{FSM}	A	2
Non-repetitive Surge peak forward current @ t=1ms square wave			2
Power dissipation	P_D	mW	200
Junction temperature	T_J	℃	-55 to +150
Storage temperature	T_{STG}	℃	-55 to +150

■ Electrical Characteristics (Ta=25℃ Unless otherwise specified)

Parameter	Symbol	Unit	Conditions	Min	Typ	Max
Reverse voltage	V_R	V	I_R=100uA	80		
Forward voltage	V_F	V	I_F=100mA			1.2
Reverse leakage current	I_R	nA	V_R=70V			100
Junction capacitance	Cj	pF	V_R=6V,f=1MHz			3.5
Reverse recovery time	Trr	ns	I_F=I_R=10mA, Irr=0.1*IR, R_L=100Ω			4

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	$R_{\theta J-A}$(1)	℃/W	625
Thermal resistance, junction-to-case	$R_{\theta J-C}$(1)	℃/W	500

Note:

（1）Device mounted on PCB, single-sided copper, with standard footprint

■Characteristics

Fig 1：P_D-Ta Curve




Fig 2：Capacitance Capability




Fig 3：Typical Forward Characteristics






Fig 4：Typical Reverse Characteristics



■Ordering Information


Preferred P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity (pcs)	Delivery mode
DAP202	F2	Approximate 0.008	3000	30000	120000	7” reel
DAP202	F4	Approximate 0.008	10000	/	210000	13” reel

■ Outline Dimensions



DIMENSIONS				
SYMBOL	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.045	0.900	1.150
A1	0.000	0.004	0.000	0.100
A2	0.035	0.041	0.900	1.050
b	0.012	0.020	0.300	0.500
c	0.004	0.008	0.100	0.200
D	0.110	0.118	2.800	3.000
E	0.047	0.055	1.200	1.400
E1	0.089	0.100	2.250	2.550
e	0.037TYP		0.950TYP	
e1	0.071	0.079	1.800	2.000
L	0.022REF		0.550REF	
L1	0.012	0.020	0.300	0.500
θ	0°	8°	0°	8°

■ Suggested Pad Layout



Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.