
STARSEA

DTC143TCA

RoHS COMPLIANT

NPN Digital Transistors (Built-in Resistors)



SOT-23


Features

●Epoxy meets UL-94 V-0 flammability rating
●Moisture Sensitivity Level 1
●Built-in bias resistors enable the configuration of an inverter circuit without connecting external input resistors
●Surface mount package ideally Suited for Automatic Insertion

Mechanical Data

● **Package**: SOT-23
● **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
● **Marking:** 03

■Equivalent circuit



(1) BASE
(2) EMITTER
(3) COLLECTOR

■**Maximum Ratings** (Ta=25℃ Unless otherwise specified)

ITEM	SYMBOL	UNIT	CONDITIONS	VALUE
Collector-Base Voltage	V_{CBO}	V	I_C=50A	50
Collector-Emitter Voltage	V_{CEO}	V	I_C=1mA	50
Emitter-Base Voltage	V_{EBO}	V	I_E=50uA	5
Collector Current	I_C	mA		100
Power Dissipation	P_D	mW		200
Junction Temperature	T_J	℃		-55 to +150
Storage Temperature	T_{STG}	℃		-55 to +150

■Electrical Characteristics (Ta=25℃ unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base voltage	V_{CBO}	V	I_C=50A	50		
Collector-emitter voltage	V_{CEO}	V	I_C=1mA	50		
Emitter-base voltage	V_{EBO}	V	I_E=50uA	5		
Collector-base cut-off current	I_{CBO}	uA	V_{CB}=50V			0.5
Emitter-base cut-off current	I_{EBO}	uA	V_{EB}=4V			0.5
DC current gain	h_{FE}		V_{CE}=5V, I_C =1mA	100		600
Input resistance	R_1	kΩ		3.29	4.7	6.11
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	I_C =5mA, I_B=0.25mA			0.3
Transition frequency	f_T	MHz	V_{CE}=10V, I_E=5mA, f=100MHz		250	

■ Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
DTC143TCA	F2	Approximate 0.009	3000	30000	120000	7” reel


■ Thermal Characteristics (Typical)


PARAMETER	SYMBOL	UNIT	VALUE
Thermal resistance, junction-to-ambient	R_{thJA} (1)	℃/W	625
Thermal resistance, junction-to-case	R_{thJC} (1)	℃/W	500


Note:1.Device mounted on PCB, single-sided copper，with standard footprint.


■ Characteristics (Typical)


Static Characteristic

















■SOT-23 Package Outline Dimensions




TOP VIEW



SIDE VIEW



SIDE VIEW



UNIT: mm

SUGGESTED SOLDER PAD LAYOUT

DIMENSIONS				
SYMBOL	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.045	0.900	1.150
A1	0.000	0.004	0.000	0.100
A2	0.035	0.041	0.900	1.050
b	0.012	0.020	0.300	0.500
c	0.004	0.008	0.100	0.200
D	0.110	0.118	2.800	3.000
E	0.047	0.055	1.200	1.400
E1	0.089	0.100	2.250	2.550
e	0.037TYP		0.950TYP	
e1	0.071	0.079	1.800	2.000
L	0.022REF		0.550REF	
L1	0.012	0.020	0.300	0.500
θ	0°	8°	0°	8°

NOTE:
1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.

Note:
1. All dimensions are in millimeters (mm) unless otherwise specified.
[所有尺寸均以毫米为单位，除非另有说明]
2. General tolerances: ±0.10mm unless otherwise specified.
[通用公差为±0.10mm，除非另有说明]
3. Dimensions and tolerances per ASME Y14.5M–2018.
[尺寸和公差遵循 ASME Y14.5M–2018 标准]
4.All dimensions shown are exclusive of burrs and gate residues. Burrs and gate vestiges shall not exceed 0.15 mm in maximum.
[所有尺寸均不包括毛刺和浇口残留。毛刺与浇口残留的尺寸最大不得超过 0.15mm]
5.Dimension b does not include dambar protrusion of max 0.100 mm per side.
[尺寸b不包括单边最大0.100 MM的中筋凸出部分]
6.Dimensions D and E are the overall extreme outer dimensions of the mold compound. These dimensions exclude mold flash, lead flash, protrusions and burrs but include the maximum allowable mold mismatch.
[D和E是塑封体的外部极限尺寸，不包括包封溢料、内引线溢料、凸出部分以及胶体毛刺，但是包含了包封错位的最大尺寸]
7.Formed leads shall be planar with respect to one another within a maximum of 0.076 mm relative to the seating plane.
[成型的管脚应为同一平面，共面性最大为0.1mm]
8. ★It is the key size.
[★ 标记为关键尺寸]

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STAR SEA's terms and conditions of sale for such products, STAR SEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STAR SEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.