
Schottky Rectifier





Features

- V_R 30V
- I_F 0.5A
- Low Forward Voltage Drop
- Moisture Sensitivity Level 1

Mechanical Data

- **Package**: SOD-123
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end
- **Marking:** SE

■ Maximum Ratings (Ta=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	Conditions	VALUE
DC Blocking Voltage	V_R	V		30
Peak forward surge current	I_{FSM}	A	8.3ms, half sine	5.5
Repetitive Peak Forward Current	I_{FRM}	A	tp=1ms，δ=0.25	2.5
Average forward current	I_{FAV}	A		0.5
Power dissipation	P_{tot}	mW		350
Thermal Resistance from junction to ambient(Note)	$R_{\theta JA}$	℃/W		286
Maximum junction temperature	T_j	℃		125
Storage temperature range	T_{stg}	℃		-55 to +125

Note：Device mounted on PCB

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

Item	Symbol	Unit	Conditions	Min	TYP	Max
Breakdown Voltage	V_R	V	I_R= 100uA	30	-	-
Reverse Leakage Current	I_R	uA	V_R=15V	-	-	20
			V_R=30V	-	-	130
Forward Voltage	V_F	V	I_F=0.1A	-	-	0.375
			I_F=0.5A	-	-	0.43
Capacitance	Cj	pF	V_R=0V, f=1MHz	-	180	-

■ Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MBR0530L	F2	Approximate 0.011	3000	30000	120000	7” reel

■ Characteristics (Typical)

Fig 1：Typical Forward Characteristics




Fig 2：Typical Reverse Characteristics






Fig 3：Capacitance Capability




■ Outline Dimensions



DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MN	MAX
A	0.140	0.152	3.550	3.850
B	0.100	0.112	2.550	2.850
C	0.055	0.071	1.400	1.800
D	0.037	0.053	0.950	1.350
E	0.020	0.028	0.510	0.710
G	0.006	---	0.150	---
H	---	0.010	---	0.250
J	---	0.006	---	0.150

■ Soldering Footprint



Note:
1. All dimensions are in millimeters (mm) unless otherwise specified.
[所有尺寸均以毫米为单位，除非另有说明]
2. General tolerances: ±0.10mm unless otherwise specified.
[通用公差为±0.10mm，除非另有说明]
3. Dimensions and tolerances per ASME Y14.5M-2018.
[尺寸和公差遵循 ASME Y14.5M-2018 标准]
4.All dimensions shown are exclusive of burrs and gate residues.
Burrs and gate vestiges shall not exceed 0.15 mm in maximum.
[所有尺寸均不包括毛刺和浇口残留。毛刺与浇口残留的尺寸最大不得超过 0.15mm]
5.Dimension b does not include dambar protrusion of max 0.100 mm per side.
[尺寸b不包括单边最大0.100 MM的中筋凸出部分]
6.Dimensions B and C are the overall extreme outer dimensions of the mold compound. These dimensions exclude mold flash, lead flash, protrusions and burrs but include the maximum allowable mold mismatch.
[B和C是塑封体的外部极限尺寸，不包括包封溢料、内引线溢料、凸出部分以及胶体毛刺，但是包含了包封错位的最大尺寸]
7.Formed leads shall be planar with respect to one another within a maximum of 0.076 mm relative to the seating plane.
[成型的管脚应为同一平面，共面性最大为0.1mm]

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.