
PNP General Purpose Amplifier



Features

- Moisture Sensitivity Level 1
- Surface mount package ideally Suited for Automatic Insertion
- Epoxy meets UL-94 V-0 flammability rating, halogen-free

Mechanical Data

- **Package**: SOT-523
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** 3N

■Maximum Ratings (Ta=25℃ Unless otherwise specified)

Item	Symbol	Unit	Conditions	Value
Collector-Emitter Voltage	V_{CEO}	V	I_C=-1.0mAdc, I_B=0	-40
Collector-Base Voltage	V_{CBO}	V	I_C=-10uAdc, I_E=0	-40
Emitter-Base Voltage	V_{EBO}	V	I_E=-10uAdc, I_C=0	-5
Collector Current	I_C	mA		-200
Collector Power Dissipation	P_C	mW		150
Thermal Resistance Junction to Ambient	$R_{\theta JA}$	℃/W		833
Operation Junction Temperature	T_J	℃		-55 to +150
Storage Temperature	T_{STG}	℃		-55 to +150

■Electrical Characteristics (Ta=25℃ unless otherwise specified)


Item	Symbol	Unit	Conditions	Min	Max
Collector-Emitter Voltage	V_{CEO}	V	I_C=-1.0mAdc, I_B=0	-40	
Collector-Base Voltage	V_{CBO}	V	I_C=-10uAdc, I_E=0	-40	
Emitter-Base Voltage	V_{EBO}	V	I_E=-10uAdc, I_C=0	-5	
Collector-base Cut-off Current	I_{CBO}	uA	V_{CB}=-40Vdc		-0.1
Emitter-base cut-off current	I_{EBO}	uA	V_{EB}=-5Vdc		-0.1
Collector-emitter Cut-off Current	I_{CEX}	uA	V_{CE}=-30Vdc,V_{EB}=-3Vdc		-0.05
DC Current Gain	h_{FE}		I_C=-0.1mAdc, V_{CE}=-1.0Vdc	60	
			I_C=-1.0mAdc, V_{CE}=-1.0Vdc	80	
			I_C=-10mAdc, V_{CE}=-1.0Vdc	100	300
			I_C=-50mAdc, V_{CE}=-1.0Vdc	60	
			I_C=-100mAdc, V_{CE}=-1.0Vdc	30	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	V	I_C=-10mAdc, I_B=-1.0mAdc		-0.25
			I_C=-50mAdc, I_B=-5.0mAdc		-0.4
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	V	I_C=-10mAdc, I_B=-1.0mAdc	-0.65	-0.85
			I_C=-50mAdc, I_B=-5.0mAdc		-0.95
Collector-base Output Capacitance	Cobo	pF	V_{CB}=-5.0Vdc, f=1.0MHz, I_E=0		4.5
Transition frequency	f_T	MHz	I_C=-10mA, V_{CE}=-20V, f=100MHz	250	
Delay Time	td	ns	V_{CC}=-3.0V,V_{BE}=-0.5V,I_C=-10mA, I_{B1}=-1.0mA	35	
Rise Time	tr	ns		35	
Storage Time	ts	ns	V_{CC}=-3.0V , I_C=-10mA, I_{B1}=I_{B2}=-1.0mA	225	
Fall Time	tf	ns		75	

■ Ordering Information (Example)


Prefered P/N	Packing Code	Unit Weight(G)	Minimum Package(Pcs)	Inner Box Quantity(Pcs)	Outer Carton Quantity(Pcs)	Delivery Mode
MMBT3906T	F2	Approximate 0.0027	3000	30000	120000	7” reel

■ **Characteristics** (Typical)


Static Characteristic




DC Current Gain




Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage




Base-Emitter On Voltage



Cob/Cib-V_{CB}/V_{EB}




■ SOT-523 Package Outline Dimensions



DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MIN	MAX
A	0.059	0.067	1.50	1.70
B	0.030	0.033	0.75	0.85
C	0.057	0.069	1.45	1.75
D	0.020TYP		0.50TYP	
E	0.035	0.043	0.90	1.10
G	0.000	0.004	0.00	0.10
H	0.024	0.031	0.60	0.80
J	0.004	0.008	0.10	0.20
K	0.006	0.014	0.15	0.35
L	0.010	0.018	0.26	0.46

■ SOT-523 Suggested Pad Layout



DIMENSIONS	
DIM	MM (TYP)
A	1.00
B	0.40
C	0.60
D	1.24
E	0.60
F	0.50

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.