
PNP Silicon High Voltage Transistor



Features

- ●Epoxy meets UL-94 V-0 flammability rating
- ●Halogen free available upon request by adding suffix "HF"
- ●Moisture Sensitivity Level 1
- ●Surface mount package ideally Suited for Automatic Insertion
- ●PNP

Mechanical Data

- **Package**: SOT-23
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** 2D

■Maximum Ratings (Ta=25℃ unless otherwise noted)

Item	Symbol	Unit	Conditions	Value
Collector-Base Voltage	V_{CBO}	V	I_C=-100μA,I_E=0	-300
Collector-Emitter Voltage	V_{CEO}	V	I_C =-1mA,I_B=0	-300
Emitter-Base Voltage	V_{EBO}	V	I_E=-100μA,I_C=0	-5
Collector Current	I_C	mA		-300
Collector Power Dissipation	P_C	mW		300
Thermal Resistance From Junction To Ambient	$R_{\theta JA}$	℃/W		417
Operation Junction Temperature	T_j	℃		-55 to +150
Storage Temperature	T_{stg}	℃		-55 to +150

■Other Characteristics（Ta=25℃ Unless otherwise specified）

Item	Symbol	Unit	Conditions	Min	Max
Transition frequency	Ft	MHz	V_{CE}=-20V,I_C=-10mA,f=30MHz	50	


■Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MMBTA92	F2	Approximate 0.009	3000	30000	120000	7" reel


■Electrical Characteristics（T_a=25℃ Unless otherwise specified）


Item	Symbol	Unit	Conditions	Min	Max
Collector-base breakdown voltage	V_{CBO}	V	I_C=-100μA,I_E=0	-300	
Collector-emitter breakdown voltage	V_{CEO}	V	I_C =-1mA,I_B=0	-300	
Emitter-base breakdown voltage	V_{EBO}	V	I_E=-100μA,I_C=0	-5	
Collector-base cut-off current	I_{CBO}	nA	V_{CB}=-200V,I_E=0		-250
Emitter-base cut-off current	I_{EBO}	nA	V_{EB}=-5V,I_C=0		-100
DC current gain	h_{FE}		V_{CE}=-10V,I_C=-1mA	60	
	h_{FE}		V_{CE}=-10V,I_C=-10mA	100	200
	h_{FE}		V_{CE}=-10V,I_C=-30mA	60	
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	I_C=-20mA,I_B=-2mA		-0.2
Base-emitter saturation voltage	$V_{BE(sat)*}$	V	I_C=-20mA,I_B=-2mA		-0.9

■Characteristics(Typical)












Base-Emitter On Voltage




Cob/Cib-V_{CB}/V_{EB}



Collector Power Derating Curve




■SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

■SOT-23 Soldering Footprint



Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.