
Dual NPN+PNP Small Signal Transistor




Features

- Epoxy meets UL-94 V-0 flammability rating
- Surface mount package ideally Suited for Automatic Insertion
- NPN/PNP

Mechanical Data

- **Package:** SOT-363
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** K27

■Equivalent circuit



■ Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MMDT2227	F2	Approximate 0.009g	3000	30000	120000	7” reel

■TR1 PNP Pin3、4、5 Maximum Ratings (Ta=25℃ Unless otherwise specified)

Item	Symbol	Unit	Conditions	Value
Collector-Base Voltage	VCBO	V	IC=-10μA,IE=0	-60
Collector-Emitter Voltage	VCEO	V	IC=-10mA,IB=0	-60
Emitter-Base Voltage	VEBO	V	IE=-10μA,IC=0	-5
Collector Current -Continuous	IC	mA		-600
Total Device Dissipation	PC	mW		200
Junction Temperature	Tj	℃		150
Storage Temperature	TSTG	℃		-55 to +150

■TR1 PNP Pin3、4、5 Electrical Characteristics (Ta=25℃ unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	TYP	Max
Collector-base breakdown voltage	V_{CBO}	V	IC=-10μA,IE=0	-60		
Collector-emitter breakdown voltage	V_{CEO}	V	IC=-10mA,IB=0	-60		
Emitter-base breakdown voltage	V_{EBO}	V	IE=-10μA,IC=0	-5		
Collector cut-off current	I_{CBO}	nA	VCB=-50V,IE=0			-10
Collector cut-off current	I_{CEX}	nA	VCE=-30V,VEB(off)=-0.5V			-50
Emmiter cut-off current	I_{EBO}	nA	VEB=-5V, IC=0			-10
DC current gain	$h_{FE}1$		VCE=-10V,IC=-0.1mA	75		
	$h_{FE}2$		VCE=-10V,IC=-1mA	100		
	$h_{FE}3$		VCE=-10V,IC=-10mA	100		
	$h_{FE}4$		VCE=-10V,IC=-150mA	100		300
	$h_{FE}5$		VCE=-10V,IC=-500mA	50		
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	IC=-150mA,IB=-15mA			-0.4
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	IC=-500mA,IB=-50mA			-1.6
Base-emitter saturation voltage	$V_{BE(sat)}$	V	IC=-150mA,IB=-15mA			-1.3
Base-emitter saturation voltage	$V_{BE(sat)}$	V	IC=-500mA,IB=-50mA			-2.6
Transition frequency	fT	MHz	VCE=-20V,IC=-50mA,f=100MHz	200		
Delay time	td	ns	VCC=-30V,IC=-150mA, IB1=-15mA			10
Rise time	tr	ns				40
Storage time	ts	ns	VCC=-6V,IC=-150mA, IB1=-IB2=-15mA			225
Fall time	tf	ns				60

■TR2 NPN Pin1、2、6 Maximum Ratings (Ta=25℃ Unless otherwise specified)


Item	Symbol	Unit	Conditions	Value
Collector-Base Voltage	VCBO	V	IC=10μA,IE=0	75
Collector-Emitter Voltage	VCEO	V	IC=10mA,IB=0	40
Emitter-Base Voltage	VEBO	V	IE=10μA,IC=0	6
Collector Current -Continuous	IC	mA		600
Total Device Dissipation	PC	mW		200
Junction Temperature	Tj	℃		150
Storage Temperature	TSTG	℃		-55 to +150

■TR2 NPN Pin1、2、6 Electrical Characteristics (Ta=25℃ unless otherwise specified)


Item	Symbol	Unit	Conditions	Min	TYP	Max
Collector-base breakdown voltage	V_{CBO}	V	IC=10μA,IE=0	75		
Collector-emitter breakdown voltage	V_{CEO}	V	IC=10mA,IB=0	40		
Emitter-base breakdown voltage	V_{EBO}	V	IE=10μA,IC=0	6		
Collector cut-off current	I_{CBO}	nA	VCB=60V,IE=0			10
Collector cut-off current	I_{CEX}	nA	VCE=60V,VEB(off)=3V			10
Emmiter cut-off current	I_{EBO}	nA	VEB=3V, IC=0			10
Base cut-off Current	I_{BL}	nA	VCE=60V,VEB(off)=3V			20
DC current gain	$h_{FE}1$		VCE=10V,IC=0.1mA	35		
	$h_{FE}2$		VCE=10V,IC=1mA	50		
	$h_{FE}3$		VCE=10V,IC=10mA	75		
	$h_{FE}4$		VCE=10V,IC=150mA	100		300
	$h_{FE}5$		VCE=1V,IC=150mA	35		
	$h_{FE}6$		VCE=10V,IC=500mA	40		
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	IC=150mA,IB=15mA			0.3
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	IC=500mA,IB=50mA			1
Base-emitter saturation voltage	$V_{BE(sat)}$	V	IC=150mA,IB=15mA			1.2
Base-emitter saturation voltage	$V_{BE(sat)}$	V	IC=500mA,IB=50mA			2
Transition frequency	fT	MHz	VCE=20V,IC=20mA,f=100MHz	300		
Delay time	td	ns	VCC=30V,IC=150mA, IB1=15mA,VBE(off)=-0.5V			10
Rise time	tr	ns				25
Storage time	ts	ns	VCC=30V,IC=150mA, IB1=- IB2=5mA			225
Fall time	tf	ns				60

■ TR1 PNP Pin3、4、5 Characteristics (Typical)


Static Characteristic




DC Current Gain




Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage



Base-Emitter On Voltage




Cob/Cib-V_{CB}/V_{EB}




■ TR2 NPN Pin1、2、6 Characteristics (Typical)


Static Characteristic




DC Current Gain




Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage




Base-Emitter On Voltage




Cob/Cib-V_{CB}/V_{EB}




■SOT-363 Package Outline Dimensions




DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MIN	MAX
A	0.035	0.043	0.9	1.1
A1	0	0.004	0	0.1
A2	0.035	0.039	0.9	1
b	0.006	0.014	0.15	0.35
c	0.002	0.01	0.05	0.25
D	0.071	0.087	1.8	2.2
E	0.045	0.053	1.15	1.35
E1	0.085	0.096	2.15	2.45
e	0.026Typ		0.65Typ	
e1	0.047	0.055	1.2	1.4
L	0.021Typ		0.525Typ	
L1	0.01	0.018	0.26	0.46
θ	0°	8°	0°	8°





■SOT-363 Soldering Footprint



Unit：mm

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.