
Dual NPN Small Signal Transistor

0



Features

- Moisture sensitivity level 1
- Halogen free and RoHS compliant
- Surface mount package ideally suited for auto matic Insertion

Application

- Signal amplification
- Switching circuit

Mechanical data

- **Package**: SOT-563
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ **Maximum Ratings** (T_a=25℃ Unless otherwise specified)

Item	Symbol	Unit	Conditions	Value
Device marking code				KAP
Collector-base voltage	V_{CBO}	V	I_C=10uA,I_E=0	60
Collector-emitter voltage	V_{CEO}	V	I_C=1mA,I_B=0	40
Emitter-base voltage	V_{EBO}	V	I_E=10uA,I_C=0	6
Collector current	I_C	mA		200
Power dissipation	P_D	mW		200
Junction temperature	T_J	℃		-55 to +150
Storage temperature	T_{STG}	℃		-55 to +150

■ Electrical Characteristics (Ta=25℃ Unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	$V_{(BR)CBO}$	V	I_C=10uA,I_E=0	60		
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	V	I_C=1mA,I_B=0	40		
Emitter-base breakdown voltage	$V_{(BR)EBO}$	V	I_E=10uA,I_C=0	6		
Base cutoff current	I_{BL}	nA	V_{CE}=30V, $V_{EB(OFF)}$=3V			50
Collector-emitter cut-off current	I_{CEX}	nA	V_{CE}=30V, $V_{EB(OFF)}$=3V			50
DC current gain	h_{FE1}		V_{CE}=1V, I_C=0.1mA	40		
	h_{FE2}		V_{CE}=1V, I_C=1mA	70		
	h_{FE3}		V_{CE}=1V, I_C=10mA	100		300
	h_{FE4}		V_{CE}=1V, I_C=50mA	60		
	h_{FE5}		V_{CE}=1V, I_C=100mA	30		
Collector-emitter saturation voltage	$V_{CE(sat)1}$	V	I_C=10mA,I_B=1mA			0.2
	$V_{CE(sat)2}$	V	I_C=50mA,I_B=5mA			0.3
Base-emitter saturation voltage	$V_{BE(sat)1}$	V	I_C=10mA,I_B=1mA	0.65		0.85
	$V_{BE(sat)2}$	V	I_C=50mA,I_B=5mA			0.95
Collector-base Output Capacitance	Cob	pF	V_{CB}=5.0V, f=1.0MHz, I_E=0			4
Transition frequency	f_T	MHz	V_{CE}=20V,I_C=10mA,f=100MHz	300		
Noise figure	N_F	dB	V_{CE}=5V,Ic=0.1mA, f=1kHz,Rg=1KΩ			5
Delay time	td	ns	V_{CC}=3V, I_C=10mA, V_{BE}=0.5V, I_{B1}=1mA			35
Rise time	tr	ns				35
Storage time	ts	ns	V_{CC}=3V, I_C=10mA, I_{B1}=-I_{B2}=1mA			200
Fall time	tf	ns				50

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	$R_{\theta J-A}$(1)	℃/W	625
Thermal resistance, junction-to-case	$R_{\theta J-C}$(1)	℃/W	500

Note:
（1）Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 25.4mm*25.4mm copper pad areas

■Characteristics

Fig 1：Static Characteristics




Fig 2：DC Current Gain




Fig 3：Collector-Emitter Saturation Voltage




Fig 4：Base-Emitter Saturation Voltage




Fig 5：Base-Emitter Voltage




Fig 6：Cob/Cib-V_{CB}/V_{EB}






Fig 7：P_D-Ta Curve



■Ordering Information


Preferred P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
MMDT3904V	F2	Approximate 0.0035	3000	30000	120000	7” reel

■ Outline Dimensions



DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MN	MAX
A	0.006	0.011	0.150	0.300
B	0.043	0.051	1.100	1.300
C	0.059	0.067	1.500	1.700
D	0.016	0.024	0.400	0.600
G	0.035	0.043	0.900	1.100
H	0.059	0.067	1.500	1.700
K	0.021	0.026	0.550	0.650
L	0.004	0.011	0.100	0.300
M	0.004	0.007	0.100	0.180

■ Suggested Pad Layout



UNIT:mm

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.