
Dual PNP Small Signal Transistor




Features

- Epoxy meets UL-94 V-0 flammability rating
- Surface mount package ideally Suited for Automatic Insertion
- PNP

Mechanical Data

- **Package:** SOT-363
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** K3N

■Equivalent circuit



■ Maximum Ratings (Ta=25℃ Unless otherwise specified)

Item	Symbol	Unit	Conditions	Value
Collector-Emitter Voltage	V_{CEO}	V	I_C=-1mAdc, I_B=0	-40
Collector-Base Voltage	V_{CBO}	V	I_C=-10uAdc, I_E=0	-40
Emitter-Base Voltage	V_{EBO}	V	I_E=-10uAdc, I_C=0	-5
Collector Current	I_C	mA		-200
Collector Power Dissipation	P_C	mW		200
Junction Temperature	T_j	℃		-55 to +150
Storage Temperature	T_{stg}	℃		-55 to +150

■ Electrical Characteristics (Ta=25℃ unless otherwise specified)


Item	Symbol	Unit	Conditions	Min	TYP	Max
Collector-base breakdown voltage	V_{CBO}	V	I_C=-10μA,I_E=0	-40		
Collector-emitter breakdown voltage	V_{CEO}	V	I_C =-1mA,I_B=0	-40		
Emitter-base breakdown voltage	V_{EBO}	V	I_E=-10μA,I_C=0	-5		
Collector-Base cut-off current	I_{CBO}	nA	V_{CB}=-30V,I_E=0			-50
Collector-emitter cut-off Current	I_{CEX}	nAdc	V_{CE}=-30Vdc, V_{BE}=-3.0Vdc			-50
Emitter-Base Cut-off current	I_{EBO}	nA	V_{EB}=-5V,I_C=0			-50
DC current gain	$h_{FE(1)}$		V_{CE}=-1V,I_C=-0.1mA	40		
	$h_{FE(2)}$		V_{CE}=-1V,I_C=-1mA	70		
	$h_{FE(3)}$		V_{CE}=-1V,I_C=-10mA	100		300
	$h_{FE(4)}$		V_{CE}=-1V,I_C=-50mA	60		
	$h_{FE(5)}$		V_{CE}=-1V,I_C=-100mA	30		
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	I_C=-10mA,I_B=-1mA			-0.25
			I_C=-50mA,I_B=-5mA			-0.4
Baser-emitter saturation voltage	$V_{BE(sat)}$	V	I_C=-10mA,I_B=-1mA	-0.65		-0.85
			I_C=-50mA,I_B=-5mA			-0.95
Collector-base Output Capacitance	Cobo	pF	V_{CB}=-5.0Vdc, f=1.0MHz, I_E=0			4.5
Transition frequency	f_T	MHz	V_{CE}=-20V,I_C=-10mA, f=100MHz	250		
Noise figure	NF	dB	V_{CE}=-5V,Ic=-0.1mA, f=1kHz,Rs=1KΩ			4

■ Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MMDT3906	F2	Approximate 0.009g	3000	30000	120000	7" reel

■ Characteristics (Typical)


Static Characteristic




DC Current Gain




Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage




Base-Emitter On Voltage




Cob/Cib-V_{CB}/V_{EB}




■SOT-363 Package Outline Dimensions



DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MIN	MAX
A	0.035	0.043	0.9	1.1
A1	0	0.004	0	0.1
A2	0.035	0.039	0.9	1
b	0.006	0.014	0.15	0.35
c	0.002	0.01	0.05	0.25
D	0.071	0.087	1.8	2.2
E	0.045	0.053	1.15	1.35
E1	0.085	0.096	2.15	2.45
e	0.026Typ		0.65Typ	
e1	0.047	0.055	1.2	1.4
L	0.021Typ		0.525Typ	
L1	0.01	0.018	0.26	0.46
θ	0°	8°	0°	8°



■SOT-363 Soldering Footprint



Unit：mm

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.