

PNP General Purpose Amplifier





SOT-323

Features

- Epoxy meets UL-94 V-0 flammability rating
- Halogen free available upon request by adding suffix ”HF”
- Moisture Sensitivity Level 1
- High Conductance
- Surface Mount Package Ideally Suited for Automatic Insertion

Mechanical Data

- **Package**: SOT-323
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** K5N

■Maximum Ratings (Ta=25℃ unless otherwise noted)

Item	Symbol	Unit	Conditions	Value
Collector-Base Voltage	V_{CBO}	V	IC=-10μA,IE=0	-40
Collector-Emitter Voltage	V_{CEO}	V	IC =-1mA,IB=0	-40
Emitter-Base Voltage	V_{EBO}	V	IE=-10μA,IC=0	-5
Collector Current	I_C	mA		-200
Collector Power Dissipation	P_C	mW		200
Operation Junction Temperature	T_j	℃		-55 to +150
Storage Temperature	T_{stg}	℃		-55 to +150

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

Item	Symbol	Unit	Conditions	Min	Max
Collector-base breakdown voltage	V_{CBO}	V	IC=-10μA,IE=0	-40	
Collector-emitter breakdown voltage	V_{CEO}	V	IC =-1mA,IB=0	-40	
Emitter-base breakdown voltage	V_{EBO}	V	IE=-10μA,IC=0	-5	
Collector-Base cut-off current	I_{CBO}	nA	VCB=-40V,IE=0		-100
Collector-Emitter cut-off current	I_{CEX}	nA	VCE=-30V, VEB=-3V,		-50
DC current gain	h_{FE}		VCE=-1V,IC=-100uA	60	
	h_{FE}		VCE=-1V,IC=-1mA	80	
	h_{FE}		VCE=-1V,IC=-10mA	100	300
	h_{FE}		VCE=-1V,IC=-50mA	60	
	h_{FE}		VCE=-1V,IC=-100mA	30	
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	IC=-50mA,IB=-5mA		-0.4
Base-emitter saturation voltage	$V_{BE(sat)*}$	V	IC=-50mA,IB=-5mA		-0.95

■Other Characteristics（T_a=25℃ Unless otherwise specified）


Item	Symbol	Unit	Conditions	Min	Max
Transition frequency	Ft	MHz	VCE=-20V,IC=-10mA,f=100MHz	250	
Delay time	td	ns	VCC=-3V,IC=-10mA, VBE(off)=-0.5V ,IB1=-1mA		35
Rise time	tr	ns			35
Storage time	ts	ns	VCC=-3V,IC=-10mA, IB1=IB2=-1mA		225
Fall time	tf	ns			75

■Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MMST3906	F2	Approximate 0.005	3000	30000	120000	7” reel

■**Characteristics**(Typical)


Static Characteristic




DC Current Gain




Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage




Base-Emitter On Voltage



Cob/Cib-V_{CB}/V_{EB}




■SOT-323 Package Outline Dimensions



DIMENSIONS					
	INCHES		MM		
DIM	MIN	MAX	MIN	MAX	NOTE
A	.071	.087	1.80	2.20	
B	.045	.053	1.15	1.35	
C	.083	.096	2.10	2.45	
D	.026 Nominal		0.65Nominal		
E	.047	.055	1.20	1.40	
F	.012	.016	.30	.40	
G	.000	.004	.000	.100	
H	.035	.039	.90	1.00	
J	.004	.010	.100	.250	
K	.006	.016	.15	.40	

■SOT-323 Soldering Footprint



MM

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.