

PBHV9050T

PNP General Purpose Amplifier





SOT-23

Features

- Moisture sensitivity level 1
- Halogen free and RoHS compliant
- Surface mount package ideally suited for automatic insertion

Application

- Signal amplification
- Switching circuit
- High voltage

Mechanical data

- **Package**: SOT-23
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ **Maximum Ratings** (T_a=25℃ Unless otherwise specified)

Item	Symbol	Unit	Conditions	Value
Device marking code				LL
Collector-base voltage	V_{CBO}	V	I_C=-100μA,I_E=0	-500
Collector-emitter voltage	V_{CEO}	V	I_C =-500uA,I_B=0	-500
Emitter-base voltage	V_{EBO}	V	I_E=-100μA,I_C=0	-6
Collector current	I_C	A		-0.15
Power dissipation	P_D	mW		300
Junction temperature	T_J	℃		-55 to +150
Storage temperature	T_{STG}	℃		-55 to +150

■ Electrical Characteristics (Ta=25℃ Unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	$V_{(BR)CBO}$	V	I_C=-100μA,I_E=0	-500		
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	V	I_C =-500uA,I_B=0	-500		
Emitter-base breakdown voltage	$V_{(BR)EBO}$	V	I_E=-100μA,I_C=0	-6		
Collector-base cut-off current	I_{CBO}	uA	V_{CB}=-360V			-0.1
Collector-emitter cut-off current	I_{CES}	uA	V_{CE}=-360V， V_{BE}=0			-0.2
Emitter-base cut-off current	I_{EBO}	uA	V_{EB}=-5V			-0.1
DC current gain	h_{FE1}		V_{CE}=-10V,I_C=-10mA	100		300
	h_{FE2}		V_{CE}=-10V,I_C=-50mA	80		300
Collector-emitter saturation voltage	$V_{CE(sat)1}$	V	I_C=-20mA,I_B=-2mA			-0.2
	$V_{CE(sat)2}$	V	I_C=-50mA,I_B=-10mA			-0.2
Base-emitter saturation voltage	$V_{BE(sat)}$	V	I_C=-50mA,I_B=-10mA			-0.9
Transition frequency	f_T	MHz	V_{CE}=-10V,I_C=-10mA,f=100MHz		50	
Collector-base output capacitance	Cob	pF	V_{CB}=-20V,f=1MHz		6	

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	RθJ-A(1)	℃/W	417
Thermal resistance, junction-to-case	RθJ-C(1)	℃/W	333

Note:

（1）Device mounted on PCB, single-sided copper， with standard footprint

■Characteristics

Fig 1：Static Characteristics




Fig 2：DC Current Gain




Fig 3：Collector-Emitter Saturation Voltage




Fig 4：Base-Emitter Saturation Voltage




Fig 5：Base-Emitter On Voltage




Fig 6：Cob/Cib-V_{CB}/V_{EB}






Fig 7：P_D-Ta Curve




■Ordering Information

Prefered P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
PBHV9050T	F2	Approximate 0.008	3000	30000	120000	7” reel
PBHV9050T	F4	Approximate 0.008	10000	/	210000	13” reel

■ Outline Dimensions






DIMENSIONS				
SYMBOL	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.045	0.900	1.150
A1	0.000	0.004	0.000	0.100
A2	0.035	0.041	0.900	1.050
b	0.012	0.020	0.300	0.500
c	0.004	0.008	0.100	0.200
D	0.110	0.118	2.800	3.000
E	0.047	0.055	1.200	1.400
E1	0.089	0.100	2.250	2.550
e	0.037TYP		0.950TYP	
e1	0.071	0.079	1.800	2.000
L	0.022REF		0.550REF	
L1	0.012	0.020	0.300	0.500
θ	0°	8°	0°	8°

Note:
1. All dimensions are in millimeters (mm) unless otherwise specified.
[所有尺寸均以毫米为单位，除非另有说明]
2. General tolerances: ±0.10mm unless otherwise specified.
[通用公差为±0.10mm，除非另有说明]
3. Dimensions and tolerances per ASME Y14.5M-2018.
[尺寸和公差遵循 ASME Y14.5M-2018 标准]
4.All dimensions shown are exclusive of burrs and gate residues. Burrs and gate vestiges shall not exceed 0.15 mm in maximum.
[所有尺寸均不包括毛刺和浇口残留。毛刺与浇口残留的尺寸最大不得超过 0.15mm]
5.Dimension b does not include dambar protrusion of max 0.100 mm per side.
[尺寸b不包括单边最大0.100 MM的中筋凸出部分]
6.Dimensions D and E are the overall extreme outer dimensions of the mold compound. These dimensions exclude mold flash, lead flash, protrusions and burrs but include the maximum allowable mold mismatch.
[D和E是塑封体的外部极限尺寸，不包括包封溢料、内引线溢料、凸出部分以及胶体毛刺，但是包含了包封错位的最大尺寸]
7.Formed leads shall be planar with respect to one another within a maximum of 0.076 mm relative to the seating plane.
[成型的管脚应为同一平面，共面性最大为0.1mm]

■ Suggested Pad Layout



Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.