
NPN General Purpose Amplifier



Features

- ●Low collectoremitter saturation voltage
- ●High current capability
- ●Improved device reliability due to reduced heat generation
- ●Epoxy meets UL94 V0 flammability rating
- ●Halogen free available upon request by adding suffix ”HF”
- ●Moisture Sensitivity Level 1
- ●Marking:3C

Applications

- ●Supply line switching circuits
- ●Battery management
- ●DC-DC convertor
- ●Strobe flash
- ●Motor and lamp driver

■Maximum Ratings (Ta=25℃)

Item	Symbol	Unit	Conditions	Value
CollectorEmitter Voltage	V_{CEO}	V	I_C=1mA, I_B=0	30
CollectorBase Voltage	V_{CBO}	V	I_C=100uA, I_E=0	40
EmitterBase Voltage	V_{EBO}	V	I_E=100uA, I_C=0	5
Collector Current	I_C	A		1
Collector Power Dissipation	Pc	mW		300
Thermal Resistance From Junction To Ambient	$R_{\theta JA}$	℃/W		417
Operation Junction Temperature	T_j	℃		150
Storage Temperature	T_{stg}	℃		-55 to +150


■Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
PBSS4130T	F2	Approximate 0.008	3000	30000	120000	7” reel

■Electrical Characteristics（T_a=25℃）


Item	Symbol	Unit	Conditions	Min	Max
CollectorEmitter Voltage	V_{CEO}	V	I_C=1mA, I_B=0	30	
CollectorBase Voltage	V_{CBO}	V	I_C=100uA, I_E=0	40	
EmitterBase Voltage	V_{EBO}	V	I_E=100uA, I_C=0	5	
Collectorbase Cutoff Current	I_{CBO}	nA	V_{CB}=30V		100
Baseemitter Cutoff Current	I_{EB0}	nA	V_{EB}=4V		100
DC Current Gain	h_{FE}		I_C=100mA V_{CE}=2V	350	
			I_C=500mA V_{CE}=2V	300	
			I_C=1A V_{CE}=2V	300	
CollectorEmitter Saturation Voltage	$V_{CE(sat)}1$	mV	I_C=100mA I_B=1mA		90
	$V_{CE(sat)}2$	mV	I_C=500mA I_B=50mA		120
	$V_{CE(sat)}3$	mV	I_C=750mA I_B=15mA		220
	$V_{CE(sat)}4$	mV	I_C=1A I_B=50mA		270
Equivalent OnResistance	$R_{CE(sat)}$	mΩ	I_C=500mA I_B=50mA		240
BaseEmitter Saturation Voltage	$V_{BE(sat)}$	V	I_C=1A I_B=100mA		1.1
BaseEmitter TurnOn Voltage	$V_{BE(on)}$	V	I_C=100mA V_{CE}=2V		0.75
Transition frequency	f_T	MHz	I_C=100mA,V_{CE}=10V,f=100MHz	100	
Collector Capacitance	Cob	pF	V_{CB}=10V,I_E=0, f=1MHz		20

■Characteristics(Typical)







Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage




Base-Emitter On Voltage




Cob/Cib-V_{CB}/V_{EB}



Collector Power Derating Curve




■SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

■SOT-23 Soldering Footprint



Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.