
NPN Transistor




Features

- Epoxy meets UL-94 V-0 flammability rating
- Halogen free available upon request by adding suffix ”HF”
- Moisture Sensitivity Level 1

Mechanical Data

- **Package**: SOT-223
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- Marking: ZT5551

■Equivalent circuit



■Maximum Ratings (Ta=25℃ unless otherwise noted)

Item	Symbol	Unit	Conditions	Value
Minimum Collector-Emitter Voltage	V_{CEO}	V	I_C=1mA, I_B=0	160
Minimum Collector-Base Voltage	V_{CBO}	V	I_C=100uA, I_E=0	180
Minimum Emitter-Base Voltage	V_{EBO}	V	I_E=10uA, I_C=0	6
Collector Current	I_C	A		0.6
Power Dissipation	P_D	W		1
Thermal Resistance From Junction To Ambient	$R_{\theta JA}$	℃/W		125
Operation Junction Temperature	T_j	℃		-55 to +150
Storage Temperature	T_{stg}	℃		-55 to +150


■Electrical Characteristics (Ta=25℃ unless otherwise noted)


Item	Symbol	Unit	Conditions	Min	Max
Collector-Emitter Voltage	V_{CEO}	V	I_C=1mAdc, I_B=0	160	-
Collector-Base Voltage	V_{CBO}	V	I_C=100uAdc, I_E=0	180	-
Emitter-Base Voltage	V_{EBO}	V	I_E=10uAdc, I_C=0	6.0	-
Collector-base Cut-off Current	I_{CBO}	nA	V_{CB}=120Vdc	-	50
Emitter-base Cut-off Current	I_{EB0}	nA	V_{EB}=4.0Vdc	-	50
DC Current Gain	h_{FE}		I_C=1.0mA V_{CE}=5.0Vdc	80	-
			I_C=10mA V_{CE}=5.0Vdc	80	250
			I_C=50mA V_{CE}=5.0Vdc	30	-
Collector-Emitter Saturation Voltage	$V_{CE(sat)1}$	V	I_C=10mA I_B =1.0mA	-	0.15
	$V_{CE(sat)2}$	V	I_C=50mA I_B =5.0mA	-	0.2
Base-Emitter Saturation Voltage	$V_{BE(sat)1}$	V	I_C=10mA I_B =1.0mA	-	1
	$V_{BE(sat)2}$	V	I_C=50mA I_B =5.0mA	-	1
Output Capacitance	C_{ob}	pF	V_{CB}=10Vdc，I_E=0，f=1MHz	-	6
Transition frequency	f_T	MHz	I_C=10mAdc, V_{CE}=5.0Vdc,f=30MHz	100	300

■Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
PZT5551	F2	Approximate 0.11	2500	5000	25000	13” reel

■Characteristics (Typical)







Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage




Base-Emitter On Voltage




Cob/Cib-V_{CB}/V_{EB}



Power Derating Curve




■SOT-223 Package Outline Dimensions



DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MN	MAX
A	0.0591	0.0670	1.5000	1.7000
A1	0.0008	0.0039	0.0200	0.1000
b	0.0259	0.0330	0.6600	0.8400
b1	0.1140	0.1220	2.9000	3.1000
c	0.0090	0.0138	0.2300	0.3500
D	0.2480	0.2640	6.3000	6.7000
E	0.2637	0.2874	6.7000	7.3000
E1	0.1290	0.1460	3.3000	3.7000
e	0.0866	0.0945	2.2000	2.4000
L	0.0295	0.0492	0.7500	1.2500
Θ	0°	10°	0°	10°

■SOT-223 Suggested Pad Layout



Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.