
NPN Transistor



Features

- Epoxy meets UL-94 V-0 flammability rating
- Halogen free available upon request by adding suffix ”HF”
- Moisture Sensitivity Level 1
- Marking: J6

■ Maximum Ratings (Ta=25℃ unless otherwise noted)

Item	Symbol	Unit	Conditions	Value
Collector-Base Voltage	V_{CBO}	V		50
Collector-Emitter Voltage	V_{CEO}	V		45
Emitter-Base Voltage	V_{EBO}	V		5
Collector Current	I_C	A		0.1
Collector Power Dissipation	P_C	W		0.2
Operation Junction Temperature	T_j	℃		150
Storage Temperature	T_{stg}	℃		-55 to +150

■ Electrical Characteristics (Ta=25℃ unless otherwise noted)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	V_{CBO}	V	IC=100uA,IE=0	50		
Collector-emitter breakdown voltage	V_{CEO*}	V	IC =0.1mA,IB=0	45		
Emitter-base breakdown voltage	V_{EBO}	V	IE=100uA,IC=0	5		
Collector-Base cut-off current	I_{CBO}	uA	VCB=50V,IE=0			0.1
Collector-Emitter cut-off current	I_{CEO}	uA	VCE=35V, IB =0			0.1
Emitter-Base cut-off current	I_{EBO}	uA	VEB=3V, IC =0			0.1
DC current gain	h_{FE}	V	VCE=5V,IC=1mA	200		1000
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	IC=100mA,IB=5mA			0.3
Base-emitter saturation voltage	$V_{BE(sat)}$	V	IC=100mA,IB=5mA			1

■CLASSIFICATION OF HFE (1)


RANK	L	H
RANGE	200-450	450-1000

■ Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
S9014	F2	Approximate 0.008	3000	30000	120000	7" reel

■ Characteristics (Typical)


Static Characteristic




DC Current Gain




Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage




Base-Emitter On Voltage



Cob/Cib-VCB/VEB




■SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

■SOT-23 Soldering Footprint



Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.